

Titus Group
Titus Precision
Technical catalog



Cabinet and Furniture Hardware Systems

Important Information

Technical information

Our catalog strives for information accuracy, but as our products are continually updated, we recommend verifying the latest specifications before placing an order. We retain the right to make unannounced changes due to ongoing product improvements.

User responsibility

Users are responsible for ensuring that our hardware suits their intended purpose. We suggest conducting appropriate tests and reaching out to our technical representatives for assessment.

Intellectual property

Titus Group possesses global intellectual property rights, including trademarks, patents, copyrights, designs, illustrations, drawings, and the proprietary knowledge embedded in our products' design and production. We also respect competitors' rights and other relevant product design rights. Our products are not known to infringe upon any intellectual property rights, but we take infringements seriously and will vigorously defend our rights within the bounds of the law.

Non-preferred articles

Items marked with * in the catalog are non-preferred and may have extended delivery times.

Trademarks

Titus and Titusonic are registered trademarks of Titus International Ltd. Lama is a registered trademark of Titus d.o.o. Dekani. WoodWelding is a registered trademark of WW SA.

Cabinet Connectors

Cabinet Connectors

Product Guide

Page

System 1

Fittings for rigid assembly systems	a highly cost-effective and rigid assembly system for factory, consumer and home assembly	1.9
-------------------------------------	---	-----

System 2

Fittings for face-boring applications	face boring applications that provide a tolerant efficient assembly	1.12
---------------------------------------	---	------

System 3

Fittings for face and edge boring	two component rigid face and edge drilling fastening	1.13
-----------------------------------	--	------

System 4

Fittings for face-boring only	a range of low-cost one-piece fittings for high volume home assembly applications	1.15
-------------------------------	---	------

System 5

Cams and dowels	a comprehensive range of cam and dowel connecting fittings for all cabinet applications	1.19
-----------------	---	------

System 6

Quickfit-Expando connectors

face boring expanding
connectors for all cabinet
applications

1.37

System 7

Heavy duty cams and dowels

high quality fittings for offices
and public furniture

1.47

Accessories

Adjustable cabinet legs, shelf supports and backfix connector

designed for easy and quick
installation

1.51

Why Choose Titus?

Titus connectors add value to furniture and to furniture manufacturing

Titus connectors improve the quality of furniture and lower the cost of manufacturing and assembly while ensuring a high degree of customer satisfaction.

The most advanced range of connectors available on the market

Precise and efficient product design. **The broadest possible range of drilling tolerances** ensures reliable assembly and consistently strong joints. **'Klix'** locking feature, the engagement of interlocking teeth on cam and dowel, to prevent joint loosening in service or transit.

Expanding function provides degrees of variation in out-of-tolerance drillings ensuring stronger joints and improved quality of furniture.

Twinstart thread for faster and more stable insertion.

Depth stop collar prevents over-insertion.

Firm tightening for greater confidence in use.

Cam locks at 230° assuring smooth tightening action and greater dowel pull-up.

Quickfit for hand dowel insertion.

Quickfit TL5, new generation steel dowel with quickfit expando technology for insertion in Ø5mm dowel holes.

Quickfit TL2, TL4 with the built-in self adjustment feature for higher drilling tolerances.

Quickloc one piece fitting for faster assembly with integrated expanding cam and dowel.

Zinc+steel dowel for optimal strength and performance.

Precise dowel manufacturing high precision of zinc and strength of steel assures 100% dimensional accuracy.

Easy and quick consumer friendly self-assembly of furniture

Self-assembly furniture offers consumers good value and instant availability of products.

With the aim of providing consumer with simpler instructions, fewer parts and an easier assembly process, Titus has significantly reduced and simplified the number of fittings traditionally required in furniture production.

Titus connectors provide consumers with easy assembly and furniture producers with increased productivity:

- reduced number of assembly parts
- easy assembly instructions
- security of packed parts during transit

CAF

Quick & Easy

Consumer Assembly Friendliness

Connectors

Information

Easy and Quick Furniture Assembly

CAF formula

CAF=Consumer Assembly Friendliness

Titus CAF formula provides a comparative measure for customer satisfaction. By using it manufacturers are able to evaluate their products internally or against those of their competitors.

While offering consumers easier and faster assembly, there are obvious advantages also for furniture manufacturers – buying, counting, bagging and stocking of fittings can be greatly reduced.

Total quantity
of parts

5 8 6 3 7
6 1 5 2 4
1 6 9 7 1
8 2 1 5 4 9

+ Actions
to assemble



× Number of
types of parts

1 2 3 4 5 6
1 2 3 4 5
1 2 3 4
1 2 3
1

(T+A)N = CAF

Minimise the numbers in the
Titus CAF™ formula
to achieve:


• High customer satisfaction

• Improved productivity

• Higher profits

How does it work?

Comparative CAF scores
to assemble a hand held
demonstrator



	T	A	N	CAF
Connecting screw (traditional assembly)	4	38	3	126
Cam & dowel with single start thread	6	21	4	108
Cam & dowel with twinstart thread	6	15	4	84
Cam & TL2 dowel (self-assembly)	6	7	4	52
Cam & TL2 dowel (factory pre-inserted)	2	3	2	10
Quickloc	2	3	1	5
Fully assembled demonstrator	1	0	1	1


Cabinet Connectors

CAF Quick & Easy

Consumer Assembly Friendliness


Consumer Assembly Friendliness - CAF principle

- Quick assembly with less parts and less assembly steps
- Simple instructions
- Easy and intuitive assembly




High drilling tolerances

- Optimal cabinet joint even in cases of inaccurate drilling
- In-built self adjustment feature ensures perfectly aligned and precise joints




Strong and reliable joints

- High performance joints
- Great cabinet strength even at repeatable assembly or disassembly
- Enhanced resilience even in more demanding applications in tall wardrobes or office furniture




Reliable and comfortable locking

- Smooth and firm tightening at 2 o'clock lock
- Great dowel pull-up for optimal performance
- Strong and reliable joint



Expando function

- Expanding sleeve on dowels assures high resistance to pull-out
- Firm fixing in the dowel hole



Factory pre-insertion

- With Quickfit TL5 and TL2 dowels
- Perfect for RTA market: easier packing and transportation
- The insertion of cams and dowels can be automated using Lama FastFit machine


System 1

Fittings for Rigid Assembly Systems

System Features

Double locking carcass screw

- Zinc diecast for precision
- Titus Double locking carcass screw makes an almost invisible connection
- Collar under the head to pull panels together
- 2nd 'lower' thread pulls against a 'faster' thread to provide maximum connection force and prevents overdriving of fastener
- Almost invisible in position
- Head can be 'fastcapped' or filled




System 1

Fittings for Rigid Assembly Systems

Double Locking Carcase Screw

- High performance from widely spaced primary thread
- Finer secondary thread provides additional holding power and positive stop (no stripping)
- Increased support for vertical panel is gained from the funnel head with collar at its base
- One-piece fitting



Technical and mounting details




Item number

Zinc


Screw 6x42 

00180 →


885




1. Insert screw to shoulder in face board



2. Screw into Ø5mm hole



3. Board joint pulled up by collar on screw



4. Board locked in place by screw





 2000 Pcs Made of zinc

System 1

Fittings for Rigid Assembly Systems

Hi-Lo™ Screw and Barrel Nut

- Hi-Lo™ screws have a twin thread for faster insertion
- ‘Hi’ threads and ‘Lo’ threads combine to give excellent pull out in chipboard
- Funnel head design means no countersinking
- Steel is case hardened for extra strength


	Technical and mounting details							
Hi-Lo™ screw								
								
 10000 Pcs (00062) 9000 Pcs (00068) 5000 Pcs (06074) 7000 Pcs (00071) 4000 Pcs (00077) 3000 Pcs (00172, 06077, 06080)	Made of steel							
Barrel nut								
								
 10000 Pcs	Made of plastic							
Screw cap 								
								
 50000 Pcs	Made of plastic							

A		D2				
Screw diameter		Total Length	Item number	Black	Phosphate	White
4	20	25	00062 →		852	
4	23	28	00068 →		852	
4	28	338	00071 →		852	
4	33	38	06074 →		852	
4	40	45	00077 →		852	
4	50	55	00172 →		852	
4	45	50	06077 →		852	
5	45	50	06080 →		852	
			01056 →	835		877
Other colors on request						
pozi, philips			01020 →	835		877
hexagon			01042 →	835		877
Other colors on request						

System 2


Fittings for Face-boring Applications

- Range of fixing blocks for multiple applications
- Face drilling only required
- Durable plastic material is flexible providing greater holding power
- Choose screw fastening or hammer insertion



Technical and mounting details

Housing (no nose)



Item number

White

02077 →

877


System 3

Fittings for Face and Edge Boring

System Features

Titus System 3 is a two component rigid face and edge drilled fastening with half turn to fasten. System 3 offers almost full concealment and wide tolerances in use.

- Automatic or in-factory placement
- Pre-location pin ensures ease of assembly
- Less than one turn of a screwdriver to fasten
- Shelf edge installation of pin means maximum shelf cut size tolerance
- Can be used on 12mm shelf panels
- No loose parts for maximum convenience in RTA
- Drawer front fixing, cabinet construction








System 3

Fittings for Face and Edge Boring

Concealed Housing

- One turn locking system reduces assembly time, both in the factory and home
- Pre-assembly feature for consumer convenience
- Choice of dowels to suit drilling
- Hi-Lo screw feature for faster insertion

	Technical and mounting details			C	D	D2						
Housing assembly 			X, Y - depends on board thickness									
 2500 Pcs	Made of plastic or zinc, plastic				12.5		03118 →	835		831	877	
Other colors on request												
Screw dowel Ø5				30		5	03165 →		883			
		X, Y - depends on board thickness										
 1000 Pcs	Made of steel											
Screw dowel Ø3				25		3	03090 →		883			
		X, Y - depends on board thickness										
 2000 Pcs	Made of steel			30		3.75	03181 →					881

System 4

Fittings for

Face-boring Only

System Features

Cost effective one piece fittings with face boring benefits

- Flush and block components
- Face-boring only
- Good tolerances
- One piece connectors
- Angledriv versions fastening with maximum driving power and flexibility
- Quickloc™ versions need only one turn to tighten for fast assembly
- Foolproof consumer home insertion


Quickloc™ One-piece connector

The integrated housing and dowel make Quickloc™ the most user-friendly and tolerant product available.


- High degree of drilling tolerance
- Push-in design
- Tool-free insertion
- Integrated expanding housing and dowel provide consistently stronger joints
- 'Klix' locking system

Quickloc™ Assembly


1. Press Quickloc into the face board



2. Assemble the panels



3. Tighten in less than one turn









System 4

Quickloc™

One Piece Expanding Connector

- An innovative, one-piece connector, capable of hand insertion
- Highly tolerant and tightens in less than one turn
- Face-bored product
- Offers a high degree of drilling tolerance and is the only connector of its type to provide pull-up of cabinet panels when tightened

							
Quickloc Ø20 flanged   		Item number		Dark brown	Black	White	Tan
2500 Pcs Made of zinc, plastic		06803 →		834	835	877	871
Quickloc Ø25 flanged   		06802 →		831	835	877	
1500 Pcs Made of zinc, plastic							

System 4

Fittings for

Face-boring Only

Flushbloc™ / Flushfix™

- The Angeldriv screw provides high level of tolerance
- Face drilling only required
- Corner joint and shelf fixing options

Technical and mounting details		Item number	Black	Dark brown	White	Zinc
Flushbloc™ assembly		02190 ➡	835	831	877	
		Other colors on request				
2500 Pcs Made of plastic						
Angeldriv screw for use with Flushfix™		flat head	00022 ➡			855
		Other colors on request				
4000 Pcs Made of zinc						





System 4

Fittings for

Face-boring Only

Minibloc™ / Twinbloc™

- One-piece connector range
- Face drilling only required
- Easy to use, foolproof home insertion
- Angeldriv screw tolerates good levels of inaccurate drilling increasing consumer confidence

		D		
		Drilling depth	Item number	Dark brown
				White
				
Technical and mounting details				
Minibloc Ø10 		11	*02120 	831
   		* Assembly with screw		
 2500 Pcs		Made of zinc, plastic		

Angeldriv screw  see page 1.17

System 5

Cams and Dowels

System Features

The most advanced cam and dowel range

Titus System 5 is a comprehensive range of cam and dowel connecting fittings with 'Klix' and Quickfit features for all cabinet applications: panel-to-panel, panel-to-hollow profile, back-to-back

Dowels

- **Quickfit TL5, 'Full metal jacket'**
a high performance Quickfit dowel for use in multiple wooden materials
- **Quickfit TL2, TL4, TL5 dowels**
a unique solution for factory pre-insertion, high level of drilling tolerances


- **Quickfit dowels**
quick hand insertion, easy assembly
- **Diecast dowels (zinc)**
precise manufacturing, optimal shape and design
- **Turned dowels (steel)**
'traditional' design, smooth surface, best strength performance
- **Combi dowels (zinc and steel)**
high precision of zinc, strength of steel, 100% dimensional accuracy and optimal performance

Titus 'Klix'™

Titus 'Klix' locking system ensures the engagement of the interlocking teeth on cam and dowel providing:


- vibration-proof joint
- rigid construction that will not loosen in service or transit

Dowel insertion time comparison



2 o'clock lock Smooth closing

Linear cam profile assures smooth, firm tightening action and greater pull-up. The cam always locks at 2 o'clock lock (230°), enabling greater consumer confidence in use while improving furniture quality.





Optimal performance and perfect joint even with inaccurate drillings.



Drilling tolerances

Optimal performance and perfect joint even with inaccurate drillings.


Zinc/Combi dowel




Quickfit TL5 dowel, Quickfit TL2 dowel



Quickfit TL4 dowel




ETHC=Edge To Hole Center



Quickfit dowels for factory insertion

Quickfit TL5, Quickfit TL4, and Quickfit TL2 are the only dowel solutions designed for factory pre-insertion

- Optimised packaging processes
- Reduced risk of quality issues and claims
- Ideal for the RTA market



System 5


Cams and Dowels

Cam5000

Highly resistant joint for strong cabinet construction

Reinforced cam evenly engages the hole and prevents cam tilting and cam bursting.

Increased joint resistance enables effective performance in wider tolerance range.



Linear cam profile

Linear cam profile ensures:


- Smooth tightening action
- Greater dowel pull-up



Cam retaining pips

Cam retaining pips ensures:


- The cam is held in position prior to assembly
- Secure cam positioning during transport and handling
- Accurate factory insertion



2 o'clock lock


Smooth and noticeable locking at the 2 o'clock position guarantees:

- always-right tightening for home assembly
- strong and rigid cabinet construction



Optimised cam profile

Optimised cam profile ensures smooth and tight joint with no gap between panels.



Optimal performance with all Titus dowels

Quickfit TL, Quickfit, Combi, end, double ended, angled and other screw-in dowels



System 5

Cams and Dowels


Quickfit Connectors

It is the fastest assembly system on the market. The Quickfit™ dowel may be inserted by hand, using only finger pressure. This eliminates the labour intensive process of screw-in assembly and the potential panel damage.


The Quickfit™ range of dowels has been extended to provide a complete family of fittings available in diameters of 5mm, 8mm, 10mm and lengths of 24mm and 34mm. These dowels are compatible with the range of Titus Ø15mm cams.

Assembly


1. Press the cam into face board





2. Insert the dowel into side panel




3. Assemble the panels



4. Tighten the cam to lock dowel



5. Assembled panels



Quickfit TL Connectors

Quickfit-TL™ dowel offers furniture manufacturers a fast assembly system providing high drilling tolerances. It has a built-in self-adjustment feature, which enables common drilling inaccuracies to be overcome.

For the self-assembly furniture consumer, Titus Quickfit-TL™ is the most consumer friendly fitting on the market. Apart from the benefit of fully tightened joints and easy locking into the same position, Quickfit-TL™ provides an exceptionally smooth action when tightened, requiring very little effort.


Drilling tolerances

Marginal inconsistencies of drilling and the problems associated with the natural movement of wood panels, no longer present problems.


Quickfit-TL™ provides a tolerance of ± 1 mm on drilling operation while ensuring that the final result is a perfectly precise and aligned joint. No other assembly fittings system can offer such tolerances and still maintain a perfect joint.

Assembly


1. Press the cam into face board




2a. Either push dowel into edge hole or...




2b. Insert the dowel into side panel



3. Assemble the panels



4. Tighten cam to lock dowel



System 5

Cams and Dowels

Quickfit TL5 'Full Metal Jacket'

Effective performance in multiple wooden materials


Smooth and noticeable locking at the 2 o'clock position guarantees:

- tight joints
- always-right tightening at home assembly
- strong and rigid cabinet construction



Strong and reliable joint



Expanding steel sleeve assures high resistance to torsion and pull-out.



High drilling tolerances

An extended dowel head design works as a positive stop against the cam and provides an ETHC tolerance of min. +/-1mm

Fully tightened joint assured even at marginal inconsistencies of drilling and problems associated with the natural movement of wood panels.




Shape of dowel sleeve

- Acts as a positive stop when face inserted
- Ensures correct insertion depth




Tool-free insertion for Ø5mm dowel holes

Quickfit TL5 reliably engages the 5mm dowel hole. It enables the usage of tool-less Quickfit dowel insertion technology across a wide range of applications.




50% less time to assemble the cabinet at home

When edge inserted the dowel engages the cam and remains securely positioned until the boards are locked together.



For maximum efficiency the insertion process can be automated using the Titus proprietary Lama FastFit machine.



Fast and easy cabinet assembly at home.

CAF Quick & Easy

Consumer Assembly Friendliness


System 5

Cams and Dowels

Zinc+steel Combi Dowels


Zinc+steel technology for optimal strength and performance

The Combi dowel combines steel and a small amount of zinc to ensure high precision and dimensional accuracy, essential to provide furniture manufacturers with the broadest possible range of drilling tolerances.




The steel neck and head provide better resistance to torsion and pull-out enabling a high performance joint

Zinc body:
Positive stop collar ensures correct insertion depth
Twinstart for faster and more stable insertion



The toroidal dowel head form transfers the forces between cam and dowel more effectively resulting in a small cam bursting force.







100% dimensional accuracy assured

System 5

Cams and Dowels

Quickfit TL5 'Full Metal Jacket'

- Drilling tolerances of +1/-1mm when edge inserted
- Expanding steel sleeve assures a strong joint, highly resistant to pull-out
- Tool-free insertion technology for Ø5mm holes in multiple wooden materials (chipboard, MDF, solid wood)
- For use with Cam5000






		A	T		
		Drilling distance	Thread length	Item number	TeraBlack
 Technical and mounting details					
Quickfit TL5 dowel		34	11.5	09652 →	956
		24	11.5	09651 →	956
		i Suitable for Cam5000 only			
 Tolerance range					
 1000 Pcs		Made of steel			

System 5

Cams and Dowels

Quickfit TL Dowels

- Available in Ø5mm and Ø8mm for panel-to-panel applications
- Suitable for use with all Ø15mm Cam3000 S and Cam5000 products
- ‘Klix’ locking feature provides a strong, vibration proof joint
- Highly tolerant in edge-inserted, TL4 also in face-inserted applications




Technical and mounting details					
	A	N	T	Item number	
	Drilling distance	Drilling depth	Thread length		
Quickfit TL2   D2=Ø5mm	24	12	11.6	05441 →	880
	34	12	11.6	05474 →	880
  2000 Pcs 1000 Pcs (05474) Made of zinc, plastic					
Quickfit TL4   3000 Pcs Made of zinc, plastic	24	12	11.2	05388 →	835
	  Hole to hole tolerance ±1 mm				

System 5

Cams and Dowels

Quickfit Dowels

- Available in Ø8mm and Ø10mm
- Suitable for use with all Ø15mm Cam3000 and Cam5000
- 'Klix' locking feature provides a strong, vibration proof joint
- Depth stop collar for accurate insertion




 Technical and mounting details		A	N	T	Item number	Dark grey
Drilling distance		Drilling distance	Drilling depth	Thread length		
Quickfit dowel Ø8mm  		24	12	11.5	05025 →	880
		34	12	11.5	05026 →	880
 2000 Pcs Made of zinc, plastic						
Quickfit dowel Ø10mm  		24	12	11.5	05052 →	880
		34	12	11.5	05050 →	880
		34	9.5	9.2	05147 →	880
 2000 Pcs Made of zinc, plastic						

System 5

Cams and Dowels


Quickfit P2F Dowels

- The only product to enable standard panel drilling and connection of panel and hollow profile
- Available in Ø8mm for panel-to-hollow metal profile applications
- For use with all Cam3000 S and Cam5000 products
- 'Klix' locking feature provides a strong, vibration proof joint

	Technical and mounting details	A	Drilling distance	Item number	Black
Quickfit P2F					
			24	05414 →	835
					
 2000 Pcs					
Made of zinc, plastic					



Combi Dowel

- High quality zinc-steel dowel with greater resistance to torsion and pull-out
- Suitable for use with all Ø12mm and Ø15mm Cam2000, Cam3000 and Cam5000 products
- 'Klix' locking feature provides a strong, vibration proof joint
- Twinstart thread for faster and reliable insertion



Technical and mounting details

Combi dowel Ø5 

 2000 Pcs



Made of steel and zinc

PH2 head PH2 head 

PH2 head 



Combi dowel M6

 1000 Pcs

Made of steel and zinc




A	N	T		
Drilling distance	Drilling depth	Thread length	Item number	Zinc
34	12	11	*09424 →	885
24	12	11	*09423 →	885
34	9	8.5	*09456 →	885
34		8	09592 →	885
34		10.5	09594 →	885
X → drilling depth of M6 insert				

System 5

Cams and Dowels

Double-ended Dowel

- Available in Ø7mm
- Suitable for use with all Ø12mm and Ø15mm Cam2000, Cam3000 and Cam5000 products
- No circlip for increased tolerance
- Available in a variety of lengths to suit most panel-to-panel applications





 Technical and mounting details		S	L	A	B		
		Lenght	Total lenght	Drilling distance	Panel thickness	Item number	Zinc plated
Dowel without circlip   		41	47.4	24	0*	05929 →	883
		61	67.4	34	0*	05757 →	883
		80	86.4	34	19	05753 →	883
		60	66.4	24	19	05778 →	883
*B=0 → no panel required							
 2000 Pcs (05929) 1000 Pcs (05757) 500 Pcs (05778) 250 Pcs (05753) Made of steel							

System 5

Cams and Dowels

Cam5000 Ø15mm

- Improved central shape for highly resistant joint
- Suitable for use with all Titus dowels
- 'Klix' locking feature provides a strong, vibration proof joint
- Cam retaining pips ensure that a cam is held in panel position prior to assembly

Technical and mounting details		B	D	e	h	Item number		
		Panel thickness	Drilling depth	Drilling for dowel	Cam height		Zinc	TeraBlack
Cam5000 cross drive PZ2 drive   	1000 Pcs Made of zinc	12/13	10.5	6 min	9.9	09695 →	885	959
		15/16	12.5	7.5-8	11.9	09690 →	885	959
		Use standard cover caps with pin=Ø4mm						
Cam5000 hexagonal drive combined drive with HEX   	1000 Pcs Made of zinc	15/16	12.5	7.5-8	11.9	09699 →	885	959
		18/19	14	9-9.5	13.2	09692 →	885	959
		Use standard cover caps with pin=Ø4mm						



Cover caps for Ø15 cams
 → see page 1.43






Made of plastic

System 5

Cams and Dowels

Cam3000 Ø15mm

- Its optimised shape provides a more efficient cam profile with smooth tightening action and greater dowel pull-up
- Suitable for use with Combi dowels, forged steel dowels, Quickfit dowels and Quickfit TL dowels
- 'Klix' locking feature provides a strong, vibration proof joint
- Cam-retaining pips ensure that a cam is held in panel position prior to assembly

 Technical and mounting details		B	D	e	h	Item number	Zinc
		Panel thickness	Drilling depth	Drilling for dowel	Cam height		
Cam3000 cross drive      1000 Pcs Made of zinc		12/13	10.5	6 min	9.9	09495 →	885
		15/16	12.5	7.5-8	11.9	09533 →	885
		Black available upon request					
Cam3000 hex drive      1000 Pcs Made of zinc	combined drive with HEX 	15/16	12.5	7.5-8	11.9	09537 →	885
		18/19	14	9-9.5	13.2	09536 →	885
		Use standard cover caps with pin=Ø4mm Black available upon request					



Cover caps for Ø12 cams





Made of plastic


→ see page 1.36

System 5

Cover Caps

- Available in a variety of colors
- Suitable for use with both pozi and hex cam drive features
- Suitable for use with various diameter cams
- Both domed and flat versions available

		X	Item number				
Technical and mounting details				Dark brown	Black	Light brown	
Cover cap Ø17 		3.3	*01029 →	831	835	867	877
				Other colors on request Works with PZ2 drive caps: 05644, 09533, 09495, 09690, 09695			
 25000 Pcs	Made of plastic						

Cover cap Ø17 			01026 →	831	835	867	877	
				Other colors on request Works with HEX drive cams: 05654, 05656, 09692, 09536, 09537				
 1000 Pcs	Made of plastic							

System 6

Information

System Features

A face boring connector family for 32mm system drilling with full range of panel and application variants for all cabinet manufacturing applications.

- Minimum drilling requirements
- Linear cam design for constant tightening loads when driving
- Angledriv feature on cam for maximum driving comfort
- Interchangeable pins for wood, plastic and steel applications
- Pins with twinstart drive for fast insertion
- Interchangeable Quickfit pin fastenings available
- Tool-less fastening capable versions
- Back-to-back fastenings for common vertical panel fixing of shelves

System 6 consists of a range of 20mm diameter housing, Quickfit™ and conventional dowels, end dowels and double ended dowels.

Housings are made from high grade plastic or zinc, with zinc cams.

Wedgefix-6 connector is a special fastener without cam, simply to snap onto a pre-inserted dowel.


Applications

Titus System 6 is ideal for use in high volume production of case goods, closet and garage storage systems. Because no


edge boring is required, it is an excellent choice for manufacturing environments with limited drilling capacity.

Side-entry Drop-on

Side-entry insertion of shelf panel: from the side or from the top




Drop-on insertion of shelf panel: only from the top
Using drop-on connections allows for one-man installation



Angledriv feature


The angledriv feature on the cam allows for the angled position of the screwdriver with the locking action creating a tight and secure joint.




System Features

Outrigger/ Non outrigger

Outrigger





Non outrigger




Expando function

Expanding housings and dowels provide a tight joint.




Assembly


1. Press the housing into face board




2. Press the dowel into side panel



3. Assemble the panels






4. Tighten the joint



System 6

Expanding Dowels

- Available in Ø5mm for panel-to-panel, panel-to-hollow profile and back-to-back applications
- Suitable for applications with all Titus Ø20 and Sys 6 housings
- 'Klix' locking feature provides a strong, vibration proof connection
- Depth stop collar for accurate insertion



 Technical and mounting details		D2		Dark grey	
		Drilling diameter for dowel thread			Item number
Dowel		5			06408 →
 D2= Ø5mm  ØD2 x 12.5					
 5000 Pcs		Made of zinc, plastic			
Dowel Ø5 x 7.5 back-to-back applications			06479 →	880	
  Ø5 x 7.5					
 5000 Pcs		Made of zinc, plastic			

System 6

Quickfit-Expando

Dowel

- Available in Ø5mm thread forms for screw-in, knock-in and/or 'spiked' hole applications
- Suitable for applications with all Titus Ø20mm and Sys 6 housings
- 'Klix' locking feature provides a strong, vibration proof connection
- Dowels feature an integral skirt which acts as a positive stop during insertion




	Technical and mounting details	C	Drilling depth for dowel thread	Item number				
Dowel Ø5 	  						Zinc	Steel
							9	06401 →
		8	06402 →	885	883			
		11.5	06406 →	885	883			

System 6

Double-ended Dowels

End Dowels

- For 16mm, 18mm and 19mm board
- Suitable for applications with all Titus Ø20mm and Sys 6 housings
- 'Klix' locking feature provides a strong, vibration proof connection





 Technical and mounting details		B		
Panel thickness	Item number		Steel	Zinc
16	06414 →			885
19	06416 →			885
Double-ended dowel    2500 Pcs Made of zinc				
19	06389 →		883	
Double-ended dowel    2500 Pcs Made of steel				

System 6

20mm Knock-in Housing

Non-outrigger

- Available in 15mm/16mm and 18mm/19mm versions for drop-on and/or side-entry applications
- Available in all-metal or plastic/metal options
- 'Klix' locking feature provides a strong vibration proof connection
- Compatible with all Sys 6 screw-in and Quickfit dowels






 Technical and mounting details		e	B	D							
		Panel thickness	Drilling depth	Item number	Maple	Brown	Light grey	Black	White	Silver	Nickel plated
Side-entry    2500 Pcs Made of plastic		7.75	15/16	12.5	06381 →	841	898		835	877	861
		9.25	18/19	14	06385 →	841	898		835	877	
		Other colors on request									
Drop-on    2500 Pcs Made of plastic		7.75	15/16	12.5	06383 →	841	898	882	835	877	
		9.25	18/19	14	06387 →	841	898	882	835	877	861
		Other colors on request									
Drop-on   500 Pcs Made of zinc		7.75	15/16	12.5	06447 →						847
		9.25	18/19	14	06449 →						847

System 6

20mm Knock-in Housing

Outrigger

- Available in 15mm/16mm and 18mm/19mm versions for drop-on and/or side-entry applications
- Available in all-metal or plastic/metal options
- 'Klix' locking feature provides a strong vibration proof connection
- Compatible with all Sys 6 screw-in and Quickfit dowels






 Technical and mounting details														
e	B	D	Item number	Maple	Brown	Light grey	Black	White	Silver	Nickel plated				
Panel thickness	Drilling depth													
9.25	18/19	14	06395 →	841	898		835	877	861					
Other colors on request														
Side-entry    1250 Pcs Made of plastic				7.75	15/16	12.5	06439 →	841	898	882	835	877		
				9.25	18/19	14	06397 →	841	898	882	835	877	861	
Other colors on request														
Drop-on    1250 Pcs Made of plastic				7.75		12.5	06455 →							847
				9.25		14	06457 →							847
Drop-on   500 Pcs Made of zinc														

System 6

Wedgefix Housing

(no Inner Cam)

- Available in 12mm, 15mm/16mm and/or 18mm/19mm versions for Quickfit-6 and/or Standard Dowel applications
- Available in a variety of plastic colors
- Wedgefix-6 housing allows easy customer hand-assembly or factory automated insertion
- When used with Quickfit-6 dowels this provides a true tool-less fastening system

 Technical and mounting details		B	D	 WhiteBlackDark brown		
		Panel thickness	Drilling depth	Item number		
For use with screw-in dowels     2500 Pcs Made of plastic		15/16	12.5	06473 →	877	835 898
		18/19	14	06465 →	877	835 898
Other colors on request						
For use with Quickfit dowels     2500 Pcs Made of plastic		15/16	12.5	06471 →	877	835 898
		18/19	14	06472 →	877	835 898
Other colors on request						

System 6






Flush 20mm Knock-in Housing

Non-outrigger



For use with dedicated drill bit only.
See below.






- A face-boring connector with the flush housing permits easy flat-pack transportation without panel damage
- Available for 19mm board thickness for drop-on and/or side-entry applications
- 'Klix' locking feature provides a strong vibration proof connection
- Compatible with all Sys6 screw-in and Quickfit dowels

 Technical and mounting details		e	B	D		
			Panel thickness	Drilling depth	Item number	White plastic
Side-entry   		9.5	19	14.2	06343 →	877
 1000 Pcs Housing made of plastic, cam made of zinc						
Drop-on   		9.5	19	14.2	06348 →	877
 1000 Pcs Housing made of plastic, cam made of zinc						
Drill bit for Flush 20mm Knock-in housing    					0435	
 1 Pcs Made of carbon steel					0436	

System 6.S

20mm Knock-in Housing

- Available in 15mm/16mm and 18mm/19mm versions for drop-on and/or side-entry applications
- Available in plastic-metal options
- 'Klix' locking feature provides a strong vibration proof connection
- Compatible with all Sys screw-in and Quickfit dowels




		Technical and mounting details												
Side-entry 				e	B	D								
				Panel thickness	Drilling depth	Item number	Maple	Brown	Light grey	Black	White	Silver	Nickel plated	
				7.75	15/16	12.5	006661 →	841	898	882	835	877	861	847
				9.25	18/19	14	006665 →	841	898	882	835	877	861	847
Product available on American and Asian market only														
Other colors on request														
 2500 Pcs		Made of plastic												
Drop-on 				e	B	D								
				Panel thickness	Drilling depth	Item number	Maple	Brown	Light grey	Black	White	Silver	Nickel plated	
				7.75	15/16	12.5	006663 →	841	898	882	835	877	861	847
				9.25	18/19	14	006667 →	841	898	882	835	877	861	847
Product available on American and Asian market only														
Other colors on request														
 2500 Pcs		Made of plastic												

System 7

High Strength Connectors

Contract Fix™ System

- High performance fastener
- Thread design gives repeatability
- Multi-drive recess
- Higher than average pull up





		Technical and mounting details		
		Item number	Zinc plated	
M6 Dowel 7x34		05971 →	883	
 				
 1000 Pcs		Made of steel		
Housing cylinder 15x12		05960 →		885
 				
 1000 Pcs		Made of zinc		
Grub screw		05917 →		885
				
 2500 Pcs		Made of zinc		

Cabinet Accessories

Adjustable Cabinet Legs





- Adjustable Legs
- Toe-kick clip

- Adjustable legs
- Wide adjustment range to fit all toe-kick heights
 - Vertical adjustment
 - Simple push on attachment to sockets
 - Weight/load capacity = 800 lbs/leg
- Toe-kick clip
- Spring design eliminates the need for drilling and fits into any position on plinth
 - The screw in version can sit in variable plinth positions
 - Toe-kick is reversible for corner applications

 Technical and mounting details		B1	H	Item number	Black
		Drilling distance	Fitting height adjustment		
Adjustable leg  300 Pcs (02653) 200 Pcs  Made of plastic Kit combinations available 002593.835.550 002666.835 (4 pcs) 002558.835 (4 pcs) 002523.835 (2 pcs) 25 Sets 002609.835.550 002666.835 (4 pcs) 002559.835 (4 pcs) 002523.835 (2 pcs) 25 Sets		24	60-90	02570 →	835
		24	92.5-150	02666 →	835
		24	125-185	02653 →	835
Leg extension  200 Pcs  Made of plastic			50	02571 →	835
Toe-kick clip 24 screw-on and press-in  600 Pcs  Made of plastic				02523 →	835

Adjustable Cabinet Legs

Base Sockets








		Technical and mounting details		Item number	Black
Socket 15mm (knock-in expansion) 					
				02560 →	835
 400 Pcs		Made of plastic			
Socket 10mm (knock in) 				02558 →	835
					
 400 Pcs		Made of plastic			
Socket (screw mount) 				02559 →	835
					
 400 Pcs		Made of plastic			

Shelf Supports

Drawer Front Adjuster (DFA)



- Shelf supports
- Retainer feature traps the shelf in place for security
 - Folding design allows the shelf to be post mounted in an assembled cabinet
 - Suits a wide range of shelf thicknesses
 - Pad for metal shelf support when using glass

- Drawer Front Adjuster
- Multi-direction adjustment +/-2mm
 - Locking screw to fasten M4 x TBD
 - Independent of drawer system
 - One piece housing

Technical and mounting details			B				
			Item number	Clear	Nickel	Dark brown	
Shelf support (push-in)  2000 Pcs Made of zinc			01825 →		847		
Shelf support retainer  4000 Pcs Made of plastic		16	01838 →	830			
		19	01843 →	830			
For glass shelves (rock-in)  1000 Pcs Made of zinc and plastic			338.9721 →		860		
Shelf support Ø3mm with pin  5000 Pcs Made of zinc			01912 →		847		
DFA housing  Adjustment range Technical and mounting details 							
 2500 Pcs Made of zinc, plastic			06309 →			831	
			Note: M4 screw required for mounting, not included.				





Shelf Q-Peg

- Easy and quick installation
- Structural cabinet stability through shelf-to-panel connection
- Minimalistic appearance
- In line with the shelf surface




Technical and mounting details

Shelf Q-Peg Square



Capacity chart



Recommended number of mounted pieces, 4 or 6 per shelf, is determined by its size in accordance with the EN 14749:2016


1000 Pcs

Made of zamak

B	D	e	H	Item number	Nickel plated	Noir
Panel thickness	Drilling depth	Edge to pin hole center	Height			
18	11.5	9	11	01924 →	847	668
16	10.3	7.75	9.75	01927 →	847	668

Backfix Connector

- Push-in design for quick installation
- Structural stability assured with Quarter turn lock
- Suitable for hardboard, chipboard, and MDF back panels
- For factory and home assembly



Technical and mounting details




Backfix

Item number

02254 →

Zinc

885

 1000 PCs

Made of zinc

Concealed Hinges

Concealed Hinges

A Comprehensive Range


T-type hinge



Quick furniture assembly and consistent performance on wide range of doors

- 3Way snap-on mounting
- Highly tolerant
- PressTo tool-free hinge cup fixing
- Touch opening for handleless furniture

S-type hinge



Simple snap-on mounting system

- Easy assembly and disassembly
- ConfidentClose
- Touch opening for handleless furniture
- Rigid attachment

Opening angle	Door thickness	Cranking	Door tab K	Mounting mode	Mounting plate type	Mounting plate height	Soft closing options	Page
95° 110° 120° 170°	15-34mm 15-26mm	0mm 5mm 9mm 17mm angled	3-9mm 3-6mm	'3Way' snap-on	cruciform linear for face frame	0mm 1mm 2mm 3mm 4mm 9mm	Damping integrated in the hinge cup Glissando add-on or stand-alone damping solutions	2.23
110° 170°	16-24mm	0mm 9mm 15mm angled	3-5mm 3-12mm	snap-on	cruciform for face frame	0mm 1mm 2mm 3mm 6mm 9mm 18mm	Damping integrated in the hinge cup Glissando add-on or stand-alone damping solutions	2.65

Concealed Hinges

Product Guide

	Cranking	Opening angle	Cup type	Page
T-type				
T-type-i 110	0mm	110°	for wood doors	2.25
	5mm	110°	for wood doors	2.25
	9mm	110°	for wood doors	2.27
	17mm	110°	for wood doors	2.27
T-type-i 110/45°	45°, 9mm	110°	for wood doors	2.29
	45°, 17mm	110°	for wood doors	2.31
T-type-i 110/90° for blind corner	90°, 17mm	110°	for wood doors	2.33
T-type-i 120	0mm	120°	for wood doors	2.35
T-type-i 170	0mm	170°	for wood doors	2.37
	5mm	170°	for wood doors	2.39
	9mm	170°	for wood doors	2.39
T-type 110	0mm	110°	for wood doors	2.41
	5mm	110°	for wood doors	2.41
	9mm	110°	for wood doors	2.43
	17mm	110°	for wood doors	2.43
T-type 110/45°	45°, 9mm	110°	for wood doors	2.45
	45°, 17mm	110°	for wood doors	2.47
T-type 110/90° for blind corner	90°, 17mm	110°	for wood doors	2.49
T-type 120	0mm	120°	for wood doors	2.51
T-type 170	0mm	170°	for wood doors	2.53
	5mm	170°	for wood doors	2.55
	9mm	170°	for wood doors	2.55
T-type for pie-cut corner cabinet			for wood doors	2.57
T-type mounting plates				2.59
T-type mounting plates for face frame cabinets				2.63

	Cranking	Opening angle	Cup type	Page
S-type				
S-type-i3 110	0mm	110°	for wood doors	2.67
	9mm	110°	for wood doors	2.67
	15mm	110°	for wood doors	2.67
S-type-i3 110/45°	45°, 9mm	110°	for wood doors	2.69
	45°, 18mm	110°	for wood doors	2.71
S-type-i3 110/90°	90°, 18mm	110°	for wood doors	2.73
S-type 110	0mm	110°	for wood doors	2.75
	9mm	110°	for wood doors	2.75
	15mm	110°	for wood doors	2.75
S-type 110/45°	45°, 9mm	110°	for wood doors	2.77
	45°, 18mm	110°	for wood doors	2.79
S-type 110/90°	90°, 18mm	110°	for wood doors	2.81
S-type 170	0mm	170°	for wood doors	2.83
	9mm	170°	for wood doors	2.85
S-type for pie-cut corner cabinet			for wood doors	2.87
S-type mounting plates				2.89
S-type mounting plates for face frame cabinets				2.93
Hinge angle restrictors				2.95
Cover caps				2.97

Cranking

Opening angle

Cup type

Page

Glissando Soft Closing Systems for Hinges

Glissando TT	2.107
Glissando TL3	2.107
Glissando TL 170	2.109
Glissando CR	2.111
Titusoft Door	2.113
Titusoft FF	2.115

TouchControl Solutions

Push Latch S3	2.119
Push Latch S2	2.123
Push Latch	2.125

Concealed Hinges


Door Overlay

How to Achieve the Desired Door Overlay?


By choosing the hinge of appropriate cranking

Concealed hinges with specific hinge arms are available for different door overlays. The most common overlays are:

■ Cabinet side
■ Door



- 1. Full overlay**
Use a hinge with 0mm cranking



- 2. Partial overlay for double doors**
Use a hinge with 5mm or 9mm cranking




- 3. Inset door**
Use a hinge with 15mm or 17mm cranking

By choosing the mounting plates of appropriate thickness

To achieve the desired overlay (x) while using a determined drilling distance (K), a mounting plate of appropriate

thickness (D) must be chosen from the enclosed table or calculated with given formula.




x	4	5	6	7	8	9
3	3	2	1	0		
K 4		3	2	1	0	
5			3	2	1	0

$D=4+K-x$

By choosing the appropriate drilling distance K



To achieve the desired door overlay (x) while using a determined mounting plate thickness (D), an appropriate drilling distance K must be chosen.



x	4	5	6	7	8	9
0				3	4	5
1			3	4	5	
D 2				5		
3	3	4	5			

Through side adjustment


Side adjustment is made by rotating the appropriate screw on the hinge arm.



Door clearance and gap

Door clearance ($F \geq F_{min}$) and gap (Z) represent the minimal necessary space needed for the correct opening and closing of the door. The minimal required values depend on the cup drilling distance (K), door thickness (V)

and the type of hinge. The minimum clearance scale can be found on product pages → see Door clearance chart. When using hinges with partial overlay the door clearance must be twice as large ($F \geq 2F_{min}$).



V	16	17	18	19	20	21	22
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5
K 4	0.3	0.5	0.7	0.9	1.2	1.6	2.1
5	0.3	0.5	0.7	0.9	1.2	1.5	2.0

Gap $Z_{min}=0$

Concealed Hinges

Hinge Cup Types

How to Mount the Hinge on the Door?


There are cup type symbols listed on product pages beside item numbers. Below you can find their explanation.

There are cup type symbols listed on product pages beside item numbers. Below you can find their explanation.






No pre-mounting

The hinge is fixed on the door with two screws.
3mm pilot holes recommended.






PressTo tool-free mounting

The hinge is inserted into cup hole and locked in place without tools



EasyFix


Quarter turn fixing for 8mm holes (interaxis 45/9.5) or 10mm holes (interaxis 48/6 and 52/5.5).







Machine insertion ready hinge cup

Pre-mounted dowels suitable for machine insertion into 8mm holes (interaxis 45/9.5) or 10mm holes (interaxis 48/6 and 52/5.5)



FastFix

Pre-mounted expanding dowels with triple-start screw for fast fixing, suitable for 8mm holes.



Concealed Hinges






Drilling Details

Drilling Patterns for Hinge Cup

Interaxis
45mm, 48mm and 52mm*

· T-type, S-type

**Available on special request → see page 0.3*

Hinge cup type			Interaxis 45mm  Drilling pattern
Screw-on ready 	Pre-mounted Ø4.5mm screws 		
Machine insertion ready 	FastFix 	EasyFix 	
Pre-mounted euro screws 			
Tool-less mounting 			

Interaxis is the distance between two holes center for fixing screws on the hinge cup.

Concealed Hinges

Mounting Plate Type


How to Fix the Mounting Plate on the Cabinet Side?

There are mounting plate type symbols listed on product pages beside item numbers. Below you can find their explanation.




Chipboard screw-on ready

Mounting plate is fixed with two chipboard screws or equivalent.
3mm pilot holes recommended.



Euro screw ready

Fixing with 6.3mm euro screws into pre-drilled 5mm holes. To choose appropriate head and length for use with this mounting plate is recommended.




Machine insertion ready

Pre-mounted dowels for machine insertion into pre-drilled 10mm holes.




Pre-mounted euro screws

Euro screws for 5mm holes are pre-mounted on the mounting plate.
Available lengths: 11mm, 13mm and 15mm




Pre-mounted expanding dowels

Pre-mounted expanding dowels for 5mm holes.
Available lengths: 7.5mm and 10.5mm



Pre-mounted Ø4.5mm screws

Mounting plate is fixed with two pre-mounted chipboard screws.
3mm pilot holes recommended.



Concealed Hinges

Hinge-to-plate Mounting


How to Assemble the Hinge and the Mounting Plate?

T-type 3Way snap-on


3Way snap-on mounting for intuitive hinge-to-plate assembly in three directions:

- from the hinge arm front
- from the hinge arm rear
- from the top

rear assembly




front assembly



top assembly




disassembly:
for disassembly press rear
lever on the hinge arm.



S-type snap-on

Door is assembled on the cabinet side simply by positioning the two hooks under the hinge arm on the outer part of the mounting plate and pressing gently on the rear part of the hinge arm.

For disassembly press the rear button on the hinge arm.



Concealed Hinges


Loads

How Many Hinges per Door?


Check the enclosed recommendation for the number of recommended hinges per door by considering door height and weight.
Hinges to be positioned as far apart as possible.

Recommendation:
Use the appropriate number of hinges, not exceeding door height and weight as shown below.

- Self-closing hinges
- Hinges without spring
- Hinges with integrated damping



T-type
T-type-i



S-type
S-type-i3

Hinges with integrated damping can be combined with non-damped hinges from standard hinge range.
A trial mounting is always recommended.


Concealed Hinges

Adjustments



Adjustment range can be found on the product pages.

Side Adjustment






Side adjustment aligns the door with the side of the cabinet.

By rotating the adjustment screw

- T-type
- S-type


Side adjustment is made by rotating the screw on the hinge arm.



Concealed Hinges

Adjustments

Height Adjustment





Height adjustment is necessary to achieve optimal vertical door position.

By rotating the cam adjuster



Height adjustment is made by rotating the cam adjuster on the mounting plate.

T-type with cam adjustable cruciform mounting plate

S-type with cam adjustable cruciform mounting plate





T-type with cam adjustable horizontal mounting plate



By releasing the fixing screws

For height adjustment the two mounting plate fixing screws have to be temporarily released while making the manual adjustment.

- T-type, S-type with non-cam adjustable cruciform mounting plate




Concealed Hinges

Adjustments



Adjustment range can be found on the product pages.

Depth Adjustment





The system enables easy adjustment of the gap between door and cabinet.

By rotating the cam adjuster

Rotate the cam adjuster on the hinge arm.



- T-type



By releasing the fixing or adjustment screw

The depth adjustment is made by temporarily releasing the adjustment screw. After the adjustment is made the screw has to be re-tightened.

- S-type




Concealed Hinges

Adjustments

Damping Adjustment

T-type-i

The damping action can be adjusted to fit different door weights and sizes which enables optimal door functioning.




Damping is factory pre-set to the medium damping value.
Turn towards '+' to increase and '-' to decrease the damping.

Key Design Choices


ConfidentClose

The hinge is designed to provide consumer preferred way of soft closing action.


Based on results of Titus researches made in UK, Germany and Slovenia



Fast closing



Late start of deceleration action




Quiet landing with SoftTouch

One-for-all efficiency principle

Damping on the hinge cup
Damper, positioned transversal to the hinge cup allows for easy introduction of hinge versions


Damped and non-damped version on one mounting plate platform



Adjustable damping

Flexibility to tune performance for all applications

- Consistent performance over a wide range of doors of different sizes and weights
- Easy accessible adjustment button for intuitive and quick adjustment




Adjustable damping zone and force

Titus Damper Inside

- Efficient damping at any closing speed
- Reliable closing
- Damping force consistency



T-type Hinges




T-type PressTo Tool-free hinge cup fixing

- Effortless press-in locking
- Confident locking action
- Reliable door attachment
- Confident and repeatable assembly




T-type-i 170

- Wide angle hinge with integrated damping
- Zero-protrusion opening angle makes it ideal for interior drawers application




3Way snap-on mounting

- Mounting from three directions: rear, front, top
- Reduced assembly time




Easy door installation even on tall and heavy door

- Easy mounting of doors with four or more hinges



Highly tolerant

- Efficient performance in edge value of tolerances
- Reliable door closing in case of accidental misalignment
- ConfidentClose assured




Rigidity


- Tight hinge-to-plate joint improves hinge stability and reduces door sag
- Enhanced door stability
- Smooth performance

T-type-i 110

For wood doors




- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system




110°
35mm
12mm,
12.5mm PressTo
3Way snap-on



Technical details



Interaxis
45mm




Cup type

Item number

Cranking

0mm



Screw-on

701.0AT0.054



Machine insertion

701.0AT1.054



FastFix

701.0AT5.054



PressTo

701.0AT6.054


Drilling patterns for hinge cups
→ see page 2.13

150 Pcs

Made of steel

Cranking

5mm



Screw-on

701.0BT0.054



Machine insertion

701.0BT1.054



FastFix

701.0BT5.054



PressTo

701.0BT6.054

Drilling patterns for hinge cups
→ see page 2.13

150 Pcs

Made of steel

Mounting plates

→ see pages 2.59-2.64




Cover caps for hinge arm

→ see page 2.97



Hinge cup screws

If not pre-mounted



820.6328.050

10000 Pcs

Hinge angle restrictor

→ see page 2.95




TouchControl solutions


→ see pages 2.119-2.126



Damping adjustment



Door adjustment



Side
adjustment
+3/-1mm



Height
adjustment
+2/-2mm

Depth
adjustment
+4/-1mm


For further explanation → see page 2.21

For further explanation → see pages 2.18-2.20

Mounting details



Mounting plate drilling distance



Mounting plate thickness table

For further explanation → see page 2.9

X	13	14	15	16	17	18	19
K	3	2	1	0			
	4	3	2	1	0		
	5		4	3	2	1	0
	6			4	3	2	1




$$D=13+K-X$$

Drawings show application on
D=0mm mounting plate

X	8	9	10	11	12	13	14
---	---	---	----	----	----	----	----

K	3	2	1	0			
	4	3	2	1	0		
	5		4	3	2	1	0
	6			4	3	2	1


$$D=8+K-X$$



Drawings show application on
D=0mm mounting plate

Door clearance at R=1mm

For further explanation → see page 2.10




V	16	17	18	19	20	21	22	23	24	25	26	
K	3	0.5	0.7	0.8	1	1.2	1.5	1.7	2.1	2.8	4.1	5.5
	4	0.4	0.7	0.8	1	1.2	1.5	1.7	2.1	2.3	3.1	4.5
	5	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	3.5
	6	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	2.9


Gap $Z_{MIN}=0$

T-type-i 110

For wood doors




- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system




110°
35mm
12mm,
12.5mm PressTo
3Way snap-on



Technical details



Interaxis
45mm




Cup type

Item number

Cranking

9mm



Screw-on

701.0CT0.054



Machine insertion

701.0CT1.054



FastFix

701.0CT5.054



PressTo

701.0CT6.054


Drilling patterns for hinge cups
→ see page 2.13

150 Pcs

Made of steel

Cranking

17mm



Screw-on

701.0DT0.054



Machine insertion

701.0DT1.054



FastFix

701.0DT5.054



PressTo

701.0DT6.054

Drilling patterns for hinge cups
→ see page 2.13

150 Pcs

Made of steel

Mounting plates

→ see pages 2.59-2.64




Cover caps for hinge arm

→ see page 2.97



Hinge cup screws

If not pre-mounted



820.6328.050

10000 Pcs

Hinge angle restrictor

→ see page 2.95




TouchControl solutions


→ see pages 2.119-2.126




Damping adjustment




Door adjustment



Side
adjustment
+3/-1mm



Height
adjustment
+2/-2mm






Depth
adjustment
+4/-1mm

For further explanation → see page 2.21

For further explanation → see pages 2.18-2.20

Mounting
details






Mounting plate
drilling distance

Mounting plate thickness table
For further explanation → see page 2.9

X	4	5	6	7	8	9	10
3	3	2	1	0			
4	4	3	2	1	0		
5		4	3	2	1	0	
6			4	3	2	1	0

$$D = 4 + K - X$$

Drawings show application on
D=0mm mounting plate




V	16	17	18	19	20	21	22	23	24
3	0	0	0	0	1	1	1	1	2
4	1	1	1	1	2	2	2	2	3
5	2	2	2	2	3	3	3	3	4
6	3	3	3	3	4	4	4	4	

$$D = -4 + K + F$$

Drawings show application on
D=2mm mounting plate

Door clearance at R=1mm

For further explanation → see page 2.10





V	16	17	18	19	20	21	22	23	24	25	26
3	0.5	0.7	0.8	1	1.2	1.5	1.7	2.1	2.8	4.1	5.5
4	0.4	0.7	0.8	1	1.2	1.5	1.7	2.1	2.3	3.1	4.5
5	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	3.5
6	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	2.9

Gap $Z_{MIN}=0$

T-type-i 110/45°

45° angled application for wood doors




- Opening angle
 - Drilling diameter for hinge cup
 - Drilling depth
 - Hinge on plate mounting system
- 110°
35mm
12mm
3Way snap-on



Technical details

Cup type



Interaxis
45mm



Item
number

Cranking

9mm



Screw-on

701.0D82.650



Machine
insertion

701.0D88.650



FastFix

701.0BY9.650

Drilling patterns for hinge cups
→ see page 2.13



100 Pcs

Cup made of steel, arm made of zinc

Mounting plates

→ see pages 2.59-2.64




Cover caps for hinge arm

→ see page 2.97



Hinge cup screws

If not pre-mounted



820.6328.050

10000 Pcs

Hinge angle restrictor

→ see page 2.95




TouchControl solutions


→ see pages 2.119-2.126



Damping adjustment




Door adjustment





For further explanation → see page 2.21

For further explanation → see pages 2.18-2.20

Mounting details



Mounting plate drilling distance



Mounting plate thickness table


For further explanation → see page 2.9

P	7	7.5	8	8.5	9	9.5	10	10.5	11	11.5	12	12.5	13	13.5
K	3	4	3		2		1		0					
	4		4		3		2		1		0			
	5			4		3		2		1		0		
	6					4		3		2		1		0

Drawings show application on D=0mm mounting plate

Door clearance at R=1mm

For further explanation → see page 2.10





V	16	17	18	19	20	21	22	23	24	25	26	
K	3	0.5	0.7	0.8	1	1.2	1.5	1.7	2.1	2.8	4.1	5.5
	4	0.4	0.7	0.8	1	1.2	1.5	1.7	2.1	2.3	3.1	4.5
	5	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	3.5
	6	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	2.9

Gap Z_{MIN}=0

T-type-i 110/45°

45° angled application for wood doors




- Opening angle
 - Drilling diameter for hinge cup
 - Drilling depth
 - Hinge on plate mounting system
- 110°
35mm
12mm
3Way snap-on



Technical details



Cup type

Interaxis
45mm



Item
number

Cranking
17mm



Screw-on

701.0B08.650

Machine insertion

701.0C78.650

FastFix

701.0899.650

Drilling patterns for hinge cups
→ see page 2.13

100 Pcs

Cup made of steel, arm made of zinc


Mounting plates
→ see pages 2.59-2.64



Cover caps for hinge arm
→ see page 2.97



Hinge cup screws
If not pre-mounted



820.6328.050

10000 Pcs


Hinge angle restrictor
→ see page 2.95



TouchControl solutions
→ see pages 2.119-2.126




Damping adjustment





For further explanation → see page 2.21

Door adjustment




For further explanation → see pages 2.18-2.20

Mounting details



Mounting plate drilling distance



Mounting plate thickness table


For further explanation → see page 2.9

P	0	0.5	1	1.5	2	2.5	3	3.5	4
K	3	2	1	0					
	4	3	2	1	0				
	5	3	2	1	0				
	6	4	3	2	1	0	D		

Drawings show application on D=0mm mounting plate

Door clearance at R=1mm

For further explanation → see page 2.10





V		16	17	18	19	20	21	22	23	24	25	26	
K	3	0.5	0.7	0.8	1	1.2	1.5	1.7	2.1	2.8	4.1	5.5	
	4	0.4	0.7	0.8	1	1.2	1.5	1.7	2.1	2.3	3.1	4.5	
	5	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	3.5	
	6	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	2.9	F _{MIN}

Gap Z_{MIN}=0

T-type-i 110/90°

For wood door cabinets with blind panels




- Opening angle
 - Drilling diameter for hinge cup
 - Drilling depth
 - Hinge on plate mounting system
- 110°
35mm
12mm
3Way snap-on



Technical details


Cup type

Interaxis
45mm



Item number

Cranking
17mm



 Screw-on	701.0A96.650
 Machine insertion	701.0D36.650
 FastFix	701.0895.650

Drilling patterns for hinge cups
→ see page 2.13

 100 Pcs

Cup made of steel, arm made of zinc


Mounting plates
→ see pages 2.59-2.64



Cover caps for hinge arm
→ see page 2.97



Hinge cup screws
If not pre-mounted



820.6328.050
 10000 Pcs

Hinge angle restrictor
→ see page 2.95




TouchControl solutions
→ see pages 2.119-2.126




- We advise combining with a D=2mm mounting plate.


Damping adjustment




Door adjustment



Side
adjustment
+2.5/-2.5mm



Height
adjustment
+2/-2mm






Depth
adjustment
+3/-1mm

For further explanation → see page 2.21

For further explanation → see pages 2.18-2.20

Mounting
details




Mounting plate
drilling distance

Drawing shows application on
D=2mm mounting plate

Door clearance at R=1mm

For further explanation → see page 2.10






V		16	17	18	19	20	21	22	23	24	25	26	
K	3	0.5	0.7	0.8	1	1.2	1.5	1.7	2.1	2.8	4.1	5.5	
	4	0.4	0.7	0.8	1	1.2	1.5	1.7	2.1	2.3	3.1	4.5	
	5	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	3.5	
	6	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	2.9	F _{MIN}

F_{MIN}

Gap Z_{MIN}=0

T-type-i 120

For wood doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system


120°
35mm
12mm
3Way snap-on



Technical details

Cup type


Interaxis
45mm



Item number

Cranking

0mm



Screw-on

701.0UT0.054



Machine insertion

701.0UT1.054



FastFix

701.0UT5.054

Drilling patterns for hinge cups
→ see page 2.13

150 Pcs

Made of steel


Mounting plates
→ see pages 2.59-2.64



Cover caps for hinge arm
→ see page 2.97



Hinge cup screws
If not pre-mounted




820.6328.050

10000 Pcs


TouchControl solutions
→ see pages 2.119-2.126



Damping adjustment





Door adjustment




For further explanation → see page 2.21

For further explanation → see pages 2.18-2.20

Mounting details



Mounting plate drilling distance



Mounting plate thickness table

For further explanation → see page 2.9


X	13	14	15	16	17	18	19
3	3	2	1	0			
4	4	3	2	1	0		
K							
5		4	3	2	1	0	
6			4	3	2	1	0
							D

$$D=13+K-X$$

Drawings show application on
D=0mm mounting plate

Door clearance at R=1mm

For further explanation → see page 2.10




V	16	17	18	19
3	1.1	0.4	0	0
K				
4	2	1.4	0.7	0.1
5	3	2.3	1.6	1
				F _{MIN}


Gap Z_{MIN} =2

T-type-i 170

For wood doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system



165°
35mm
12mm,
12.5mm PressTo
3Way snap-on




Technical details

Cup type	Interaxis 45mm
Item number	

Cranking

0mm



	701.0ET0.054
	701.0ET1.054
	701.0ET5.054
	701.0ET6.054

Drilling patterns for hinge cups
→ see page 2.13


50 Pcs

Made of steel and zinc

Mounting plates
→ see pages 2.59-2.64



Hinge cup screws
If not pre-mounted



820.6328.050
 10000 Pcs


Hinge angle restrictor
→ see page 2.95




TouchControl solutions
→ see pages 2.119-2.126



Zero protrusion
with D=0 mounting plate



Door adjustment





For further explanation → see pages 2.18-2.20

Mounting
details

Mounting plate
drilling distance

Mounting plate thickness table
For further explanation → see page 2.9



Drawings show application on
D=0mm mounting plate
No door protrusion in
90° position


X	13	14	15	16	17	18	19	20
3	3	2	1	0				
4	4	3	2	1	0			
5		4	3	2	1	0		
6			4	3	2	1	0	
7				4	3	2	1	0

$D=13+K-X$

C value with D=0 mounting plate

K	3	4	5	6	7
	-9.0	-8.1	-7.1	-6.1	-5.2

Door clearance at R=1mm
For further explanation → see page 2.10




V	16	17	18	19	20	21	22	23	24
3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
K 5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.6
7	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.1



Gap $Z_{MIN}=0.5$

T-type-i 170

For wood doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system



165°
35mm
12mm,
12.5mm PressTo
3Way snap-on




Technical details

Cup type

Interaxis



45mm



Item number

Cranking

5mm



Screw-on

701.0FT0.054



Machine insertion

701.0FT1.054



FastFix

701.0FT5.054



PressTo

701.0FT6.054



Drilling patterns for hinge cups
→ see page 2.13

50 Pcs

Made of steel and zinc

Cranking

9mm



Screw-on

701.0GT0.054



Machine insertion

701.0GT1.054



FastFix

701.0GT5.054



PressTo

701.0GT6.054

Drilling patterns for hinge cups
→ see page 2.13

50 Pcs

Made of steel and zinc

Mounting plates

→ see pages 2.59-2.64




Cover caps for hinge arm

→ see page 2.97



Hinge cup screws

If not pre-mounted



820.6328.050

10000 Pcs

Hinge angle restrictor

→ see page 2.95




TouchControl solutions


→ see pages 2.119-2.126



Zero protrusion
with D=0 mounting plate



Door adjustment




For further explanation → see pages 2.18-2.20

Mounting
details

Mounting plate
drilling distance


Mounting plate thickness table
For further explanation → see page 2.9



Drawings show application on
D=0mm mounting plate

X	8	9	10	11	12	13	14
3	3	2	1	0			
4	4	3	2	1	0		
5		4	3	2	1	0	
6			4	3	2	1	0

$$D=8+K-X$$




Drawings show application on
D=0mm mounting plate

Drawing show application on
D=0mm mounting plate

X	1	2	3	4	5	6	7	8	9	10	11
3	6			3	2	1	0				
4		6			3	2	1	0			
5			6			3	2	1	0		
6				6			3	2	1	0	
7					6			3	2	1	0

$$D=4+K-X$$

Door clearance at R=1mm
For further explanation → see page 2.10




V	16	17	18	19	20	21	22	23	24
3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.6
7	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.1


Gap $Z_{MIN}=0.5$

T-type 110

For wood doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system






110°
35mm
12mm
3Way snap-on



Technical details

Cup type	Interaxis 45mm
Item number	

Cranking
0mm




	702.0AK0.054
	702.0AK1.054
	702.0AK5.054

i Technical and drilling details
→ see page 2.13

150 Pcs

Made of steel

Cranking
5mm



	702.0BK0.054
	702.0BK1.054
	702.0BK5.054

Drilling patterns for hinge cups
→ see page 2.13

150 Pcs

Made of steel


Mounting plates
→ see pages 2.59-2.64



Cover caps for hinge arm
→ see page 2.97



Hinge cup screws
If not pre-mounted



820.6328.050
 10000 Pcs

Hinge angle restrictor
→ see page 2.95




TouchControl solutions
→ see pages 2.119-2.126



Soft closing systems
→ see pages 2.107-2.116





Door adjustment




For further explanation → see pages 2.18-2.20

Mounting details



Drawings show application on D=0mm mounting plate

Mounting plate drilling distance





Mounting plate thickness table


For further explanation → see page 2.9

X	13	14	15	16	17	18	19
3	3	2	1	0			
4	4	3	2	1	0		
K							
5		4	3	2	1	0	
6			4	3	2	1	0
							D

$$D=13+K-X$$



Drawings show application on D=0mm mounting plate




x	8	9	10	11	12	13	14
3	3	2	1	0			
4	4	3	2	1	0		
K							
5		4	3	2	1	0	
6			4	3	2	1	0
							D

$$D=8+K-X$$

Door clearance at R=1mm

For further explanation → see page 2.10






V	16	17	18	19	20	21	22	23	24	25	26
3	0.5	0.7	0.8	1	1.2	1.5	1.7	2.1	2.8	4.1	5.5
4	0.4	0.7	0.8	1	1.2	1.5	1.7	2.1	2.3	3.1	4.5
K											
5	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	3.5
6	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	2.9
											F _{MIN}

Gap Z_{MIN}=0

T-type 110

For wood doors




- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

110°
35mm
12mm
3Way snap-on



Technical details

Interaxis
45mm





Cup type

Item number

Cranking

9mm



Screw-on

702.0CK0.054



Machine insertion

702.0CK1.054



FastFix

702.0CK5.054


Drilling patterns for hinge cups
→ see page 2.13

150 Pcs

Made of steel

Cranking

17mm



Screw-on

702.0DK0.054



Machine insertion

702.0DK1.054



FastFix

702.0DK5.054

Drilling patterns for hinge cups
→ see page 2.13

150 Pcs

Made of steel

Mounting plates

→ see pages 2.59-2.64




Cover caps for hinge arm

→ see page 2.97



Hinge cup screws

If not pre-mounted



820.6328.050

10000 Pcs

Hinge angle restrictor

→ see page 2.95



TouchControl solutions

→ see pages 2.119-2.126




Soft closing systems

→ see pages 2.107-2.116




Door adjustment




For further explanation → see pages 2.18-2.20

Mounting details



Drawings show application on D=0mm mounting plate

Mounting plate drilling distance



Mounting plate thickness table

For further explanation → see page 2.9


X	4	5	6	7	8	9	10
3	3	2	1	0			
4	4	3	2	1	0		
5		4	3	2	1	0	
6			4	3	2	1	0

$$D=4+K-X$$

V	16	17	18	19	20	21	22	23	24
---	----	----	----	----	----	----	----	----	----

3	0	0	0	0	1	1	1	1	2
4	1	1	1	1	2	2	2	2	3
5	2	2	2	2	3	3	3	3	4
6	3	3	3	3	4	4	4	4	D


$$D=-4+K+F$$



Drawings show application on D=2mm mounting plate

Door clearance at R=1mm

For further explanation → see page 2.10





V	16	17	18	19	20	21	22	23	24	25	26
3	0.5	0.7	0.8	1	1.2	1.5	1.7	2.1	2.8	4.1	5.5
4	0.4	0.7	0.8	1	1.2	1.5	1.7	2.1	2.3	3.1	4.5
5	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	3.5
6	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	2.9

Gap Z_{MIN}=0

T-type 110/45°

45° angled application for wood doors




- Opening angle
 - Drilling diameter for hinge cup
 - Drilling depth
 - Hinge on plate mounting system
- 110°
35mm
12mm
3Way snap-on



Technical details



Cup type

Interaxis
45mm



Item
number

Cranking
9mm



Screw-on

702.0D81.650

Machine insertion

702.0D87.650

FastFix

702.0797.650

Drilling patterns for hinge cups
→ see page 2.13

100 Pcs

Cup made of steel, arm made of zinc


Mounting plates
→ see pages 2.59-2.64



Cover caps for hinge arm
→ see page 2.97



Hinge cup screws
If not pre-mounted



820.6328.050

10000 Pcs

Hinge angle restrictor
→ see page 2.95




TouchControl solutions
→ see pages 2.119-2.126



Soft closing systems
→ see pages 2.107-2.116




Door adjustment




For further explanation → see pages 2.18-2.20

Mounting details



Drawings show application on
D=0mm mounting plate

Mounting plate drilling distance




Mounting plate thickness table

For further explanation → see page 2.9

P	7	7.5	8	8.5	9	9.5	10	10.5	11	11.5	12	12.5	13	13.5
3	4		3		2		1		0					
4			4		3		2		1		0			
5				4		3		2		1		0		
6						4		3		2		1		0

Door clearance at R=1mm

For further explanation → see page 2.10





V	16	17	18	19	20	21	22	23	24	25	26
3	0.5	0.7	0.8	1	1.2	1.5	1.7	2.1	2.8	4.1	5.5
4	0.4	0.7	0.8	1	1.2	1.5	1.7	2.1	2.3	3.1	4.5
5	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	3.5
6	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	2.9

Gap Z_{MIN}=0

T-type 110/45°

45° angled application for wood doors




- Opening angle
 - Drilling diameter for hinge cup
 - Drilling depth
 - Hinge on plate mounting system
- 110°
35mm
12mm
3Way snap-on



Technical details



Interaxis
45mm



Cup type

Item number

Cranking
17mm



Screw-on

702.0B07.650



Machine insertion

702.0C77.650



FastFix

702.0879.650

Drilling patterns for hinge cups
→ see page 2.13

 100 Pcs

Cup made of steel, arm made of zinc


Mounting plates
→ see pages 2.59-2.64



Cover caps for hinge arm
→ see page 2.97



Hinge cup screws
If not pre-mounted



820.6328.050

 10000 Pcs

Hinge angle restrictor
→ see page 2.95




TouchControl solutions
→ see pages 2.119-2.126



Soft closing systems
→ see pages 2.107-2.116




Door adjustment




For further explanation → see pages 2.18-2.20

Mounting details



Drawings show application on
D=0mm mounting plate


Mounting plate drilling distance



Mounting plate thickness table
For further explanation → see page 2.9

P	0	0.5	1	1.5	2	2.5	3	3.5	4
K	3	2		1		0			
	4	3	2		1		0		
	5		3	2		1		0	
	6	4		3	2		1		0

Door clearance at R=1mm
For further explanation → see page 2.10





V		16	17	18	19	20	21	22	23	24	25	26
K	3	0.5	0.7	0.8	1	1.2	1.5	1.7	2.1	2.8	4.1	5.5
	4	0.4	0.7	0.8	1	1.2	1.5	1.7	2.1	2.3	3.1	4.5
	5	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	3.5
	6	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	2.9
		F _{MIN}										

Gap Z_{MIN}=0

T-type 110/90°

For wood door cabinets with blind panels




- Opening angle
 - Drilling diameter for hinge cup
 - Drilling depth
 - Hinge on plate mounting system
- 110°
35mm
12mm
3Way snap-on



Technical details


Interaxis
45mm



Cup type

Item number

Cranking
17mm



Screw-on

702.0A95.650



Machine insertion

702.0D35.650



FastFix

702.0689.650

Drilling patterns for hinge cups
→ see page 2.13

 100 Pcs

Cup made of steel, arm made of zinc


Mounting plates
→ see pages 2.59-2.64



Cover caps for hinge arm
→ see page 2.97



Hinge cup screws
If not pre-mounted



820.6328.050

 10000 Pcs

Hinge angle restrictor
→ see page 2.95




TouchControl solutions
→ see pages 2.119-2.126



Soft closing systems
→ see pages 2.107-2.116




· We advise combining with a D=2mm mounting plate.





For further explanation → see pages 2.18-2.20

Mounting details




Drawing shows application on D=2mm mounting plate



Mounting plate drilling distance

Door clearance at R=1mm
For further explanation → see page 2.10






V		16	17	18	19	20	21	22	23	24	25	26
K	3	0.5	0.7	0.8	1	1.2	1.5	1.7	2.1	2.8	4.1	5.5
	4	0.4	0.7	0.8	1	1.2	1.5	1.7	2.1	2.3	3.1	4.5
	5	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	3.5
	6	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	2.9 F _{MIN}

Gap Z_{MIN}=0

T-type 120

For wood doors




- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

120°
35mm
12mm
3Way snap-on



Technical details




Cup type

Item number

Cranking

0mm



Screw-on

702.0UK0.054



Machine insertion

702.0UK1.054



FastFix

702.0UK5.054

Drilling patterns for hinge cups
→ see page 2.13

150 Pcs

Made of steel


Mounting plates
→ see pages 2.59-2.64



Cover caps for hinge arm
→ see page 2.97



Hinge cup screws
If not pre-mounted



820.6328.050

10000 Pcs


TouchControl solutions
→ see pages 2.119-2.126



Soft closing systems
→ see pages 2.107-2.116




Door adjustment




For further explanation → see pages 2.18-2.20

Mounting details



Drawings show application on
D=0mm mounting plate

Mounting plate drilling distance



Mounting plate thickness table


For further explanation → see page 2.9

X	13	14	15	16	17	18	19
3	3	2	1	0			
4	4	3	2	1	0		
K							
5		4	3	2	1	0	
6			4	3	2	1	0
							D

$$D=13+K-X$$

Door clearance at R=1mm

For further explanation → see page 2.10






V	16	17	18	19
3	1.1	0.4	0	0
K				
4	2	1.4	0.7	0.1
5	3	2.3	1.6	1
				F _{MIN}

Gap Z_{MIN} =2

T-type 170

For wood doors




- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

165°
35mm
12mm
3Way snap-on



Technical details

Interaxis
45mm





Cup type

Item number

Cranking

0mm



Screw-on

702.0EK0.054



Machine insertion


702.0EK1.054



FastFix

702.0EK5.054

Drilling patterns for hinge cups
→ see page 2.13




50 Pcs

Made of steel and zinc

Mounting plates
→ see pages 2.59-2.64



Hinge cup screws
If not pre-mounted



820.6328.050

10000 Pcs

Hinge angle restrictor
→ see page 2.95




TouchControl solutions
see pages 2.119-2.126




Soft closing systems
→ see page 2.109



Zero protrusion
with D=0 mounting plate




Door adjustment




For further explanation → see pages 2.18-2.20

Mounting
details



Drawings show application on
D=0mm mounting plate
No door protrusion in
90° position

Mounting plate
drilling distance



Mounting plate thickness table

For further explanation → see page 2.9

X	13	14	15	16	17	18	19	20
3	3	2	1	0				
4	4	3	2	1	0			
5		4	3	2	1	0		
6			4	3	2	1	0	
7				4	3	2	1	0


$$D=13+K-X$$

C value with D=0 mounting plates

K	3	4	5	6	7
C	-9.0	-8.1	-7.1	-6.1	-5.2

Door clearance at R=1mm

For further explanation → see page 2.10






V	16	17	18	19	20	21	22	23	24
3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.6
7	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.1

Gap Z_{MIN}=0.5

T-type 170

For wood doors




- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system


165°
35mm
12mm
3Way snap-on



Technical details

Cup type	Interaxis 45mm
	
Item number	

Cranking
5mm





	702.0FK0.054
	702.0FK1.054
	702.0FK5.054

Drilling patterns for hinge cups
→ see page 2.13

 50 Pcs

Made of steel and zinc

Cranking
9mm



	702.0GK0.054
	702.0GK1.054
	702.0GK5.054

Drilling patterns for hinge cups
→ see page 2.13


 50 Pcs

Made of steel and zinc

Mounting plates
→ see pages 2.59-2.64



Hinge cup screws
If not pre-mounted



820.6328.050
 10000 Pcs

Hinge angle restrictor
see page 2.95




TouchControl solutions
→ see pages 2.119-2.126



Soft closing systems
→ see page 2.109




Door adjustment




For further explanation → see pages 2.18-2.20

Mounting details



Drawings show application on
D=0mm mounting plate

Mounting plate drilling distance




Mounting plate thickness table


For further explanation → see page 2.9

X	8	9	10	11	12	13	14
3	3	2	1	0			
4	4	3	2	1	0		
5		4	3	2	1	0	
6			4	3	2	1	0

$$D=8+K-X$$



Drawings show application on
D=0mm mounting plate




Drawing show application on
D=0mm mounting plate

X	1	2	3	4	5	6	7	8	9	10	11
3	6			3	2	1	0				
4		6			3	2	1	0			
5			6			3	2	1	0		
6				6			3	2	1	0	
7					6			3	2	1	0

$$D=4+K-X$$

Door clearance at R=1mm

For further explanation → see page 2.10



V	16	17	18	19	20	21	22	23	24
3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.6
7	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.1


F_{MIN}

Gap Z_{MIN}=0.5

T-type

for Pie-cut Corner Cabinet


For wood doors



- Opening angle
 - Drilling diameter for hinge cup
 - Drilling depth
 - Hinge on plate mounting system
- 70°/25°
35mm
12mm
3Way snap-on





Technical details



Cup type

Item number

Corner cabinet



Screw-on	721.0PK0.650
Fast-fix	721.0PK5.650

Drilling patterns for hinge cups
 → see page 2.13

50 Pcs

Cup made of zinc, arm made of steel


Mounting plates
 → see pages 2.59-2.64



Cover caps for hinge arm
 → see page 2.97



Hinge cup screws
 If not pre-mounted




820.6328.050
 10000 Pcs

TouchControl solutions
 → see pages 2.119-2.126




- Use in pair with 170° hinge
- Cam adjustment
- Standard cup drilling - no extra cutting needed




For further explanation → see pages 2.18-2.20

Mounting details




Mounting plate drilling distance




Any T-type mounting plate can be used

Adjustments




Drawings show application on D=2mm mounting plate

The adjustment of the gap between two doors is done by rotating the adjustment screw as shown on the drawing



T-type Mounting Plates



3Way snap-on mounting



Cam adjustable cruciform
mounting plate 37mm

Drilling pattern



Dimensions



150 Pcs

Made of steel

Cam adjustable linear
mounting plate




150 Pcs


Made of steel and zinc






Mounting plate thickness



Height adjustment +2/-2mm



Height adjustment +2/-2mm

Mounting plate type	 15	 10.5	 10.5	 15	
Mounting plate thickness (D)	 min 11.5 Ø5	 min 10.5 Ø10	 min 10.5 Ø5	no pre-drilling required  min 15	
Item number					
0mm	700.0KC0.054	700.0KB0.054	700.0KF0.054	700.0KA0.054	
3mm	700.0KC3.054	700.0KB3.054	700.0KF3.054	700.0KA3.054	
0mm	700.0LC0.650	700.0LB0.650	700.0LF0.650		
3mm	700.0LC3.650	700.0LB3.650	700.0LF3.650		

Legend of mounting plate type symbols



Pre-mounted
15mm euro screws







Machine
insertion ready




Pre-mounted
10.5mm
expanding dowels



Pre-mounted
chipboard screw





T-type Mounting Plates



Cruciform mounting plate 37mm

Drilling pattern


Dimensions



150 Pcs

Made of steel

Fixing screw for cruciform mounting plate
If not pre-mounted




Chipboard screws
820.6328.050




10000 Pcs








Mounting plate thickness



Height adjustment +2/-2mm




Height adjustment +2/-2mm

Mounting plate type		 15	 10.5	 10.5	 14.5	
Mounting plate thickness (D)						
Item number						
0mm	700.0NA0.054	700.0NC0.054	700.0NB0.054	700.0NF0.054	700.0NE0.054	
3mm	700.0NA3.054	700.0NC3.054	700.0NB3.054	700.0NF3.054	700.0NE3.054	

Legend of mounting plate type symbols




Screw-on ready for chipboard screws
← screws




 15

Pre-mounted 15mm euro screws




 10.5

Machine insertion ready




 10.5

Pre-mounted 10.5mm expanding dowels



 14.5


Pre-mounted chipboard screw



T-type

Mounting Plates for Face Frame Cabinets



3Way snap-on mounting



Cam adjustable
face frame mounting plate

Drilling pattern




Dimensions



150 Pcs

Made of steel and zinc


Cam adjustable
face frame mounting plate inset mounting



150 Pcs

Made of steel and zinc


Fixing screw for cruciform mounting plate
If not pre-mounted




Chipboard screws
820.6328.050




10000 Pcs




Mounting plate thickness



Height adjustment +2/-2mm



Height adjustment +2/-2mm


Mounting plate type		
		
Mounting plate thickness (D)	Item number	Item number
		
0mm		700.0KW0.650
3mm		700.0KW3.650
6mm		700.0KW6.650
inset	700.0KWN.054	

Legend of mounting plate type symbols


Screw-on ready for
chipboard screws
← screws




S-type Hinges




Snap-on mounting system

- Easy and quick assembly and disassembly
- Flexibility for the furniture user
- Tight hinge-to-plate joint improves hinge stability and reduces door sag




Easily accesible height adjustment with cam

- Intuitive and quick height adjustment
- Consumer friendly




ConfidentClose

- 1 Fast closing
- 2 Late start of deceleration action
- 3 Quiet landing with SoftTouch




Titus Damper Inside

- Titus proprietary multi-purpose damping technology
- Reliable and consistent life-long damping



Soft closing options

- Integrated
- Glissando add-on
- Stand-alone






Touch opening

- Guarantees effortless opening
- Elegant cabinet design
- Doors without handles

S-type-i3 110

For wood doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system


110°
35mm
min. 11mm
snap-on



Technical details

Cup type

Interaxis
45mm



Item number


Cranking
0mm



200 Pcs



Made of steel and plastic



Screw-on

242.0970.054




Pre-mounted
Ø4.5mm screws

242.0A00.054

Drilling patterns for hinge cups
→ see page 2.13


Cranking
9mm



200 Pcs



Made of steel and plastic




Screw-on

242.0976.054

Drilling patterns for hinge cups
→ see page 2.13


Cranking
15mm



200 Pcs



Made of steel and plastic



Screw-on

242.0997.054

Drilling patterns for hinge cups
→ see page 2.13


Mounting plates
→ see pages 2.89-2.94



Cover caps for hinge arm
→ see page 2.97



Hinge cup screws
If not pre-mounted



820.6308.050

10000 Pcs


Hinge angle restrictor
→ see page 2.95



TouchControl solutions
→ see pages 2.119-2.126





Door adjustment




For further explanation → see pages 2.18-2.20

Mounting details



Drawings show application on
D=0mm mounting plate

Mounting plate drilling distance





Mounting plate thickness table


For further explanation → see page 2.9

X	13	14	15	16	17	18
3	3	2	1	0		
K	4	3	2	1	0	
5			3	2	1	0

$$D=13+K-X$$





Drawings show application on
D=0mm mounting plate




X	4	5	6	7	8	9
3	3	2	1	0		
K	4	3	2	1	0	
5			3	2	1	0

$$D=4+K-X$$



Drawings show application on
D=3mm mounting plate




V	16	17	18	19	20	21
3	2	2	2	3	3	3
K	4	3	3			
5	3					

$$D=-2+K+F$$

Door clearance

For further explanation → see page 2.10





V	16	17	18	19	20	21	22
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5
K	4	0.3	0.5	0.7	0.9	1.2	1.6
5	0.3	0.5	0.7	0.9	1.2	1.5	2.0

Gap $Z_{MIN}=0$

S-type-i3 110/45°

45° angled application for wood doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system


110°
35mm
min. 11mm
snap-on



Technical details

Cup type

Interaxis
45mm



Item number



 Screw-on

242.0P81.650

Drilling patterns for hinge cups
→ see page 2.13

Cranking

9mm



 100 Pcs

Cup made of steel and plastic, arm made of zinc


Mounting plates
→ see pages 2.89-2.94



Cover caps for hinge arm
→ see page 2.97



Hinge cup screws
If not pre-mounted



820.6308.050

 10000 Pcs


Hinge angle restrictor
→ see page 2.95



TouchControl Solutions
→ see pages 2.119-2.126




Door adjustment




For further explanation → see pages 2.18-2.20

Mounting details



Mounting plate drilling distance



Mounting plate thickness table


For further explanation → see page 2.9

P	9	9.5	10	10.5	11	11.5	12	12.5	13.5
3	3		2		1		0		
K 4		3		2		1		0	
5				3		2		1	0
									D

Drawing show application on
D=3mm mounting plate

Door clearance

For further explanation → see page 2.10





V	16	17	18	19	20	21	22
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5
K 4	0.3	0.5	0.7	0.9	1.2	1.6	2.1
5	0.3	0.5	0.7	0.9	1.2	1.5	2.0

Gap $Z_{MIN}=0$

S-type-i3 110/45°

45° angled application for wood doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system


110°
35mm
min. 11mm
snap-on



Technical details

Cup type

Interaxis
45mm





Item number

 Screw-on

242.0G76.650

Drilling patterns for hinge cups
→ see page 2.13

Cranking
18mm



 100 Pcs

Cup made of steel and plastic, arm made of zinc


Mounting plates
→ see pages 2.89-2.94



Cover caps for hinge arm
→ see page 2.97



Hinge cup screws
If not pre-mounted



 **820.6308.050**

 10000 Pcs


Hinge angle restrictor
→ see page 2.95



TouchControl Solutions
→ see pages 2.119-2.126




Door adjustment




For further explanation → see pages 2.18-2.20

Mounting details



Mounting plate drilling distance



Mounting plate thickness table
For further explanation → see page 2.9

K	3	4	5	
	0	1	2	D

Drawing shows application on
D=0mm mounting plate

Door clearance
For further explanation → see page 2.10





V	16	17	18	19	20	21	22	
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5	
K	4	0.3	0.5	0.7	0.9	1.2	1.6	2.1
	5	0.3	0.5	0.7	0.9	1.2	1.5	2.0 F _{MIN}

Gap Z_{MIN}=0

S-type-i3 110/90°

For wood door cabinets with blind panels



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system


110°
35mm
min. 11mm
snap-on



Technical details

Cup type

Interaxis
45mm




Item number

 Screw-on

242.0Y45.650

Drilling patterns for hinge cups
→ see page 2.13

Cranking
18mm



 100 Pcs

Cup made of steel and plastic, arm made of zinc


Mounting plates
→ see pages 2.89-2.94



Cover caps for hinge arm
→ see page 2.97



Hinge cup screws
If not pre-mounted



 820.6308.050

 10000 Pcs


Hinge angle restrictor
→ see page 2.95



TouchControl Solutions
→ see pages 2.119-2.126




Door adjustment





For further explanation → see pages 2.18-2.20

Mounting details



Drawings show application on D=0mm mounting plate


Mounting plate drilling distance



Drawing shows application on D=3mm mounting plate
Door aligned with blind panel

Door clearance

For further explanation → see page 2.10






V	16	17	18	19	20	21	22
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5
K 4	0.3	0.5	0.7	0.9	1.2	1.6	2.1
5	0.3	0.5	0.7	0.9	1.2	1.5	2.0

F_{MIN}

Gap Z_{MIN}=0

S-type 110

For wood doors




- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

110°
35mm
11.5mm
snap-on



Technical details


Interaxis
45mm



Cup type

Item number


Cranking
0mm



200 Pcs



Made of steel



Screw-on


248.0535.050

Machine insertion

248.0171.050

Drilling patterns for hinge cups
→ see page 2.13


Cranking
9mm



200 Pcs



Made of steel



Screw-on


248.0536.050

Machine insertion

248.0279.050

Drilling patterns for hinge cups
→ see page 2.13


Cranking
15mm



200 Pcs



Made of steel



Screw-on

248.0537.050

Machine insertion

248.0280.050

Drilling patterns for hinge cups
→ see page 2.13


Mounting plates
→ see pages 2.89-2.94



Cover caps for hinge arm
→ see page 2.97



Hinge cup screws
If not pre-mounted



820.6308.050

10000 Pcs

Hinge angle restrictor
→ see page 2.95




TouchControl Solutions
→ see pages 2.119-2.126



Soft closing systems
→ see pages 2.107-2.116




Door adjustment




For further explanation → see pages 2.18-2.20

Mounting details





Mounting plate drilling distance



Mounting plate thickness table For further explanation → see page 2.9



X	13	14	15	16	17	18	
3	3	2	1	0			
K	4	3	2	1	0		
5			3	2	1	0	D

$$D=13+K-X$$



X	4	5	6	7	8	9	
3	3	2	1	0			
K	4	3	2	1	0		
5			3	2	1	0	D

$$D=4+K-X$$




V	16	17	18	19	20	21	
3	2	2	2	3	3	3	
K	4	3	3	3			
5	3						D

$$D=-2+K-F$$

Door clearance

For further explanation → see page 2.10





V	16	17	18	19	20	21	22	
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5	
K	4	0.3	0.5	0.7	0.9	1.2	1.6	2.1
5	0.3	0.5	0.7	0.9	1.2	1.5	2.0	F _{MIN}

Gap Z_{MIN}=0

S-type 110/45°

45° angled application for wood doors




- Opening angle
 - Drilling diameter for hinge cup
 - Drilling depth
 - Hinge on plate mounting system
- 110°
35mm
11.5mm
snap-on



Technical details



Cup type

Interaxis
45mm



Item
number

Cranking
9mm



Screw-on

248.0433.050

Machine
insertion

248.0N16.050

Drilling patterns for hinge cups
→ see page 2.13

200 Pcs

Cup made of steel, arm made of zinc


Mounting plates
→ see pages 2.89-2.94



Cover caps for hinge arm
→ see page 2.97



Hinge cup screws
If not pre-mounted



820.6308.050

10000 Pcs

Hinge angle restrictor
→ see page 2.95




TouchControl Solutions
→ see pages 2.119-2.126



Soft closing systems
→ see pages 2.107-2.116




Door adjustment




For further explanation → see pages 2.18-2.20

Mounting details



Drawings show application on
D=3mm mounting plate

Mounting plate drilling distance




Mounting plate thickness table For further explanation → see page 2.9

P	9	9.5	10	10.5	11	11.5	12	12.5	13.5
3	3		2		1		0		
K 4		3		2		1		0	
5				3		2		1	0
									D

Door clearance

For further explanation → see page 2.10





V	16	17	18	19	20	21	22
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5
K 4	0.3	0.5	0.7	0.9	1.2	1.6	2.1
5	0.3	0.5	0.7	0.9	1.2	1.5	2.0
							F _{MIN}

Gap Z_{MIN}=0

S-type 110/45°

45° angled application for wood doors




- Opening angle
 - Drilling diameter for hinge cup
 - Drilling depth
 - Hinge on plate mounting system
- 110°
35mm
11.5mm
snap-on



Technical details

Interaxis
45mm



Cup type

Item number






248.0285.050



248.0N20.050

Drilling patterns for hinge cups
→ see page 2.13

Cranking
18mm



100 Pcs

Cup made of steel, arm made of zinc


Mounting plates
→ see pages 2.89-2.94




Cover caps for hinge arm
→ see page 2.97



Hinge cup screws
If not pre-mounted



820.6308.050



Hinge angle restrictor
→ see page 2.95




TouchControl Solutions
→ see pages 2.119-2.126



Soft closing systems
→ see pages 2.107-2.116




Door adjustment




For further explanation → see pages 2.18-2.20

Mounting details




Drawings show application on D=0mm mounting plate



Drawing shows application on D=0mm mounting plate

Mounting plate drilling distance



Mounting plate thickness table
For further explanation → see page 2.9

K	3	4	5	
	0	1	2	D

Door clearance
For further explanation → see page 2.10





V	16	17	18	19	20	21	22	
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5	
K	4	0.3	0.5	0.7	0.9	1.2	1.6	2.1
5	0.3	0.5	0.7	0.9	1.2	1.5	2.0	F _{MIN}

Gap Z_{MIN}=0

S-type 110/90°

For wood door cabinets with blind panels




- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

110°
35mm
11.5mm
snap-on



Technical details


Interaxis
45mm



Cup type

Item number

Cranking
18mm



Screw-on

248.0745.050



Machine insertion

248.0N24.050

Drilling patterns for hinge cups
→ see page 2.13

 100 Pcs

Cup made of steel, arm made of zinc


Mounting plates
→ see pages 2.89-2.94



Cover caps for hinge arm
→ see page 2.97



Hinge cup screws
If not pre-mounted



 **820.6308.050**

 10000 Pcs

Hinge angle restrictor
→ see page 2.95




TouchControl Solutions
→ see pages 2.119-2.126



Soft closing systems
→ see pages 2.107-2.116




Door adjustment




For further explanation → see pages 2.18-2.20

Mounting details


Mounting plate drilling distance



Drawings show application on
D=0mm mounting plate




Drawing shows application on
D=3mm mounting plate
Door aligned with blind panel



Door clearance

For further explanation → see page 2.10






V	16	17	18	19	20	21	22	
3	0.3	0.5	0.7	1.0	1.3	1.7	2.5	
K 4	0.3	0.5	0.7	0.9	1.2	1.6	2.1	
5	0.3	0.5	0.7	0.9	1.2	1.5	2.0	F _{MIN}

Gap Z_{MIN}=0


S-type 170

For wood doors



- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system


170°
35mm
12mm
snap-on



Technical details

Cup type



Interaxis
45mm



Item number

Cranking

0mm



Screw-on

248.0R14.050

Machine insertion

248.0M73.050

Drilling patterns for hinge cups
→ see page 2.13


50 Pcs

Made of steel and zinc

Mounting plates
→ see pages 2.89-2.94



Hinge cup screws
If not pre-mounted



820.6308.050

10000 Pcs

Hinge angle restrictor
→ see page 2.95




TouchControl Solutions
→ see pages 2.119-2.126




Soft closing systems
→ see page 2.109



Zero protrusion
with D=0 mounting plate



Door adjustment





For further explanation → see pages 2.18-2.20

Mounting
details

Mounting plate
drilling distance

Mounting plate thickness table
For further explanation → see page 2.9



X	10	11	12	13	14	15	16	17	18	19	20
3	6			3	2	1	0				
4		6			3	2	1	0			
K 5			6			3	2	1	0		
6				6			3	2	1	0	
7					6			3	2	1	0
											D

$$D=13+K-X$$


C value with D=0 mounting plates

K	3	4	5	6	7
	-9.0	-8.1	-7.1	-6.1	-5.2
					C

Drawings show application on
D=0mm mounting plate
No protrusion in 90° position

Door clearance

For further explanation → see page 2.10






V	16	17	18	19	20	21	22	23	24
3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
K 5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.6
7	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.1
									F _{MIN}

Gap Z_{MIN}=0.5

S-type 170

For wood doors




- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

170°
35mm
12mm
snap-on



Technical details

Interaxis
45mm





Cup type

Item
number

Cranking


9mm



Screw-on

248.0162.050

Drilling patterns for hinge cups
→ see page 2.13




50 Pcs

Made of steel and zinc


Mounting plates
→ see pages 2.89-2.94



Hinge cup screws
If not pre-mounted



820.6308.050



10000 Pcs

Hinge angle restrictor
→ see page 2.95




TouchControl Solutions
→ see pages 2.119-2.126



Soft closing systems
→ see page 2.109





Door adjustment




For further explanation → see pages 2.18-2.20

Mounting details



Mounting plate drilling distance



Mounting plate thickness table For further explanation → see page 2.9


X	1	2	3	4	5	6	7	8	9	10	11
3	6			3	2	1	0				
4		6			3	2	1	0			
K 5			6			3	2	1	0		
6				6			3	2	1	0	
7					6			3	2	1	0

$$D=4+K-X$$


C value with D=0 mounting plates

K	3	4	5	6	7
C	0	0.9	1.9	2.9	3.8


Drawings show application on D=0mm mounting plate



Drawing shows application on D=0mm mounting plate




Drawing shows application on D=9mm mounting plate



Drawing shows application on D=18mm mounting plate

Door clearance For further explanation → see page 2.10




V	16	17	18	19	20	21	22	23	24
3	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
K 5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.6
7	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	5.1

Gap Z_{MIN}=0.5

S-type

for Pie-cut Corner Cabinet

For wood doors




- Opening angle
- Drilling diameter for hinge cup
- Drilling depth
- Hinge on plate mounting system

90°
35mm
11.5mm
snap-on



Technical details

Interaxis
45mm



Cup type

Item number

Screw-on



248.0U21.050

Machine insertion

248.0U22.050

Drilling patterns for hinge cups
→ see page 2.13

Corner cabinet



100 Pcs

Cup made of steel, arm made of zinc


Mounting plates
→ see pages 2.89-2.94



Cover caps for hinge arm
→ see page 2.97



Hinge cup screws
If not pre-mounted



820.6308.050


10000 Pcs

TouchControl Solutions
→ see pages 2.119-2.126




· Use in pair with 170° hinge

Door adjustment




For further explanation → see pages 2.18-2.20


Mounting details




Mounting plate drilling distance



Adjustments



The diagonal adjustment is made by rotating the appropriate screw as shown on the drawing





Drawing shows application on $D=3\text{mm}$ mounting plate

S-type

Mounting Plates



S-type snap-on mounting



Cam adjustable cruciform
mounting plate 37mm


Drilling pattern

Dimensions



200 Pcs

Made of steel



Mounting plate thickness

Height adjustment +/- 2mm

Mounting plate type	13	15	15	10.5	10.5	
Mounting plate thickness (D)						
Item number						
0mm	244.0258.050	244.0261.050	*244.0264.050	*244.0342.050	244.0270.050	
3mm	244.0260.050	244.0263.050	*244.0266.050	*244.0344.050	244.0272.050	

* Available upon special request —> see page 0.3

Legend of mounting plate type symbols

13
 Pre-mounted
 13mm euro screws

15
 Pre-mounted
 15mm euro screws


15
 Pre-mounted
 chipboard screws

10.5
 Machine
 insertion ready

10.5
 Pre-mounted
 10.5mm
 expanding dowels

S-type Mounting Plates



S-type snap-on mounting



Cruciform mounting plate



Drilling pattern

Dimensions




 200 Pcs Made of steel

Zinc diecast cruciform
mounting plate 37mm




 200 Pcs Made of zinc

Fixing screws for mounting plates
If not pre-mounted



Euro screws
821.6304.050 L=11
821.6323.050 L=13
821.6332.050 L=15

 5000 Pcs




Chipboard screws
820.6328.050









 10000 Pcs







Mounting plate thickness



Height adjustment +/- 2mm

Mounting plate type			 11	 13	 15	 15	 10.5	 10.5
Mounting plate thickness (D)								
Item number								
0mm	244.1136.050	*244.1233.050	244.0Z26.050	244.0134.050	244.0118.050	*244.0136.050	*244.0166.050	244.0P26.050
3mm	244.1139.050	*244.1234.050		244.0135.050	244.0119.050	*244.0137.050	*244.0167.050	244.0P27.050
* Available upon special request —> see page 0.3 Mounting plates with pre-mounted 7.5mm expanding dowels available upon special request —> see page 0.3								
9mm	244.3651.650			244.0M33.650	244.0P29.650			
18mm	244.3016.650			244.0085.650	244.0095.650			

Legend of mounting plate type symbols

		 11	 13	 15	 15	 10.5	 10.5
Screw on ready for euro screws ← screws	Screw-on ready for chipboard ← screws	Pre-mounted 11mm euro screws	Pre-mounted 13mm euro screws	Pre-mounted 15mm euro screws	Pre-mounted chipboard screws	Machine insertion ready	Pre-mounted 10.5mm expanding dowels
							




S-type

Mounting Plates


for Face Frame

Cabinets

S-type snap-on mounting


	Drilling pattern	Dimensions
Face frame adapter for S-type hinges 		
 200 Pcs	Made of zinc alloy	

Fixing screw for mounting plates
If not pre-mounted



Chipboard screws
820.6328.050

 10000 Pcs



Mounting plate thickness


Height adjustment +/- 2mm

Mounting plate type		
Mounting plate thickness (D)	 Item number	
0mm	244.3653.650	
3mm	244.3654.650	
6mm	244.3655.650	

Legend of mounting plate type symbols




Screw-on ready for chipboard screws
← screws




Hinge Angle Restrictors





For all Titus Hinges with 110° and 170° opening angle

For 110 hinges




For 170 hinges




		Technical details	Item number	Light grey
80° Hinge Angle Restrictor T-type		For all T-type 110°	728.4669 →	380
  				
 200 Pcs		Made of plastic		
80° Hinge Angle Restrictor S-type		For all S-type 110°	248.4668 →	380
  				
 200 Pcs		Made of plastic		
135° Hinge Angle Restrictor		For all 170° hinges	248.4672 →	380
  				
 200 Pcs		Made of plastic		

- Hinge angle restrictor limits opening angle
- Prevents door damage
- Easy and quick mounting and dismounting


Mounting details




Open the door to approximately 75° and position angle restrictor to follow the hinge cup form




Push to fully open. Audible click indicates angle restrictor is in the right position




Close the door to remove the restrictor holder (cracks by itself while closing the door)



Hinge has to be in closed position



Insert angle restrictor into the hinge cup







When angle restrictor is in the right position push it down

Recommended to insert angle restrictor while doors are not mounted on the cabinet

Cover Caps

For 110 hinges

For hinge arms


		Technical details		Logo	Item number	 Nickel plated
T-type		 	Titus	728.1286 →	054	
			without	728.1283 →	054	
			Not for 5mm, 9mm, 17mm hinge cranking			
 5000 Pcs Made of steel						
T-type		 	Titus	728.1287 →	054	
			without	728.1284 →	054	
			For all T-type range			
 5000 Pcs Made of steel						
S-type		 	Titus	248.1646 →	050	
			without	248.1712 →	050	
 4000 Pcs Made of steel						

Glissando Soft Closing Systems for Hinges




ConfidentClose

- 1 Fast closing
- 2 Late start of deceleration action
- 3 Quiet landing with 'SoftTouch'




Tool-less mounting

- Reduced assembly time
- Flexible usage also as a retrofit option



Consistent Performance

- Only one Glissando for two to three hinges
- Allows for consistent performance on a wide range of door dimensions and weights



One-for-all

- One item fits multiple applications
- Same item can be used on all crankings and angled hinges



Titus Damper Inside

- Titus proprietary multi-purpose damping technology
- Efficient modular design
- Reliable and consistent damping

Glissando Add-on

Soft Closing Range

How to Choose the Right Glissando?

Glissando TT
Glissando TL3
Glissando TL 170
Glissando CR
Glissando AL

Titus Glissando soft closing system is available for the whole range of hinge applications. The user can choose between add-on or stand-alone solutions.

Concealed hinges	Add-on hinge soft closing solutions			Stand-alone door soft closing solution	
	Glissando TT	Glissando TL3	Glissando TL 170	Glissando CR	Glissando AL
T-type 95	X			X	X
T-type 110	X			X	X
T-type 110/45°	X				
T-type 110/90°	X				
T-type 120	X			X	X
T-type 170			X	X	X
S-type 110		X		X	X
S-type 110/45°		X			
S-type 110/90°		X			
S-type 170			X	X	X






Titus Glissando soft closing devices can't be used with unsprung and reverse spring hinges.

Glissando TT 'One-for-all'

T-type


- One item fits multiple applications
- Same item can be used on all crankings and angled hinges
- Designed to fit the concealed hinge cup
- Tool-less mounting
- Suitable for different types of cabinets for kitchens, living rooms, bathrooms and other furniture



Glissando TL3 'One-for-all'

S-type

- One item fits multiple applications
- Same item can be used on all crankings and angled hinges
- Adjustable damping enables perfect functioning on every door
- Designed to fit the concealed hinge cup
- Tool-less mounting
- Suitable for different types of cabinets for kitchens, living rooms, bathrooms and other furniture




S-type 110
0mm



S-type 110
9mm



S-type 110
15mm



S-type 110/15°
9mm



S-type 110/24°
9mm



S-type 110/30°
9mm



S-type 110/45°
9mm



S-type 110/45°
18mm



S-type 110/90°
18mm



Glissando



Number per Door and Positioning

How Many Glissandos per Door?

Add-on hinge soft closing solution

Glissando TT
Glissando TL3
Glissando TL 170


Number of Glissando per door depends on door dimensions, door weight, hinge arrangement. Trial mounting is recommended.



Stand-alone soft closing solution

Glissando CR
Glissando AL

Mount Glissando CR/AL on the hinged side of the cabinet on the top or bottom.




Glissando

Mounting


How to Mount Glissando?

Tool-less mounting

Glissando TL3
Glissando TT
Glissando TL 170



Simple tool-less assembly: Insert Glissando into the holes on the hinge and press down with hand.




The tool-less 'snap on' version for reduced assembly time and flexibility of application. Glissando TL can be mounted at any time after furniture assembly so can be offered as a retro fit option by the installer.

Screw-on into the cabinet corner

Glissando CR


Glissando CR is mounted into the cabinet corner by using chipboard screws 20mm long.

Glissando dampers' discreet design enhances the look of the door and occupies minimal space in the cabinet interior.




Screw-on onto the mounting plate

Glissando AL



Position the mounting plate below the hinge arm and fix with two screws. Use hinge mounting plate as a reference.



Slide Glissando AL onto the mounting plate

Glissando

Damping Adjustment

How to Adjust Damping?


Add-on hinge soft closing solution

Glissando TL 170


Glissando features quarter turn adjustment to provide optimal closing speed for any door dimensions and weight.

The damping function can be adjusted to fit different door weights which enables

- perfect door functioning
- use of the same type of Glissando for various doors



Adjustable damping zone




Turn towards '+' to increase and '-' to decrease the damping

Stand-alone soft closing solution


Glissando CR
Glissando AL

Turn towards '+' to increase or towards '-' to decrease the damping.



Damping adjustment

- Simple mounting
- Intuitive damping adjustment




Turn towards '+' to increase and '-' to decrease the damping



Glissando TT

Glissando TL3

Add-on Hinge Damper

For 95°, 110° and 120° hinges




		Technical details	Hinge opening angle	Item number
Glissando TT • T-type 95 • T-type 110 • T-type 120   200 Pcs Made of steel and plastic			95°, 110°, 120°	729.0K71.054
			110°	951.0D45.054
Glissando TL3 • S-type 110   200 Pcs Made of steel and plastic				

- Same item can be used on most of crankings and angled hinges
- Intuitive snap-on mounting
- Low protrusion in cabinet interior
- Consistent performance across a broad range of furniture doors

Mounting details


Tool-less mounting



Insert Glissando TL3 into the holes on the hinge

Press down



Dismounting details



Use flat screwdriver

A trial mounting is always recommended.



Recommended number of Glissandos per door



Glissando TL 170

Add-on Hinge Damper

For T-type 170, S-type 170 hinges




Technical details

Glissando TL 170


Hinge opening angle	Item number
170°	951.0F15.650



Soft closing mechanism



Striking plate




Box content
100 pcs soft closing mechanisms
100 pcs striking plates

 100 Pcs Made of steel, plastic and zinc

- Gentle and reliable soft closing on doors with wider opening angle
- Fits perfectly 45/9.5mm, 48/6mm and 52/5.5mm hinge cups
- ConfidentClose
- Tool-less mounting


Damping adjustment




Turn towards '+' to increase and '-' to decrease the damping

Mounting details


Tool-less mounting




Insert Glissando TL 170 into the holes on the hinge cup



Press down




Place the striking plate into the hole on the hinge arm



Press down


Recommended number of Glissandos per door



Glissando CR

Stand-alone Damper

For full overaly and half overaly
concealed hinges




Technical details

Glissando CR
for full overlay
hinges



Nominal 11
(Adjustment: Nominal + 5mm)




 100 Pcs Made of plastic

Glissando CR
for half overlay
hinges



Nominal 10
(Adjustment: Nominal + 5mm)




 100 Pcs Made of plastic

Hinge opening angle	Cranking	Item number			
			White housing	Grey housing	Beige housing
110°	0mm, 5mm	972.0X19 →↔	350	380	360
*Fixing screw included in a set					
110°	9mm, 17mm	972.0X34 →↔		380	
*Fixing screw included in a set					



- Intuitive 'place and fix' installation in the corner of the cabinet
- Tool-less damping adjustment
- One item for a wide range of doors
- Reliable performance
- Can be paired with all self-closing hinges

Damping adjustment




Turn towards '+' to increase and towards '-' to decrease the damping



Mounting details




Mount Glissando CR on the hinged side of the cabinet



One screw fixing




Mount Glissando CR on the hinged side of the cabinet



One screw fixing




The functioning of Glissando CR depends of the hinge's closing force. A trial mounting is always recommended.




Titusoft Door

For overlay doors on frame
and frameless cabinets



Titusoft Door


Technical details

Item number	  		
	White housing	Grey housing	Nickel plated

972.0F09 →	350	380	650
------------	-----	-----	-----



Nominal 11
(Adjustment: Nominal + 5mm)



 100 Pcs Made of plastic

Titusoft Door Pro


972.0X21 →		380	
------------	--	-----	--



 100 Pcs Made of plastic


- Intuitive 'Place&Fix' installation in the corner of the cabinet
- Tool-less damping adjustment
- One item for a wide range of doors
- Reliable performance

Damping adjustment




Turn towards '+' to increase and towards '-' to decrease the damping

Mounting details




Mount Titusoft Door on the hinged side of the cabinet


Fixing



One screw fixing




Mount Titusoft Door on the hinged side of the cabinet



One screw fixing

A trail mounting is always recommended. Please contact Titus Group or your local distributor for further technical assistance.





Recommended number per door

Titusoft FF

Soft Closing System for Face Frame Cabinets with Wooden Drawer

For wooden drawer
with roller runners



Technical details

Item number

Grey

White

Titusoft FF

Titusoft
mechanism

973.0M99 →

380

Activator


973.4451 →

380


350



Titusoft mechanism



Activator



Bag of 1

973.0M99.380.K1  300 Bags


- 1 Titusoft mechanism
- 1 activator grey
- 2 screws Ø3.5mm x 25mm
- 2 screws Ø3.5mm x 12mm
- 1 mounting instruction sheet



250 Pcs

Made of plastic


- Works with most roller runner drawer slides
- Easy, intuitive mounting
- Smooth, soft closing action independent of drawer hardware
- Non-handed design



Mount 1 or 2 Titusoft mechanisms depending on drawer weight and width


Mounting details

1.




Position the Titusoft on the top of a drawer slide

2.




Screw the Titusoft mechanism to the face frame

3.



Align the activator with the top of the Titusoft mechanism and fix with two screws

4.



Fix with 2 (3) screws L=12mm


A trial mounting is always recommended. Please contact Titus Group or your local distributor for further technical assistance.

TouchControl Solutions



Push Latch S3

- Soft push opening system controls the outward motion for smooth, silent, and bounceless door movement
- Integrated damper ensures a soft landing, protecting the cabinet and enhancing user comfort




Built-in SafeGuard

- For enhanced safety, adjustment button can't be removed
- Prevents from misuse



Noir, elegant and discreet dark finish

- Seamless integration of hardware into the furniture
- Uniform and discreet surface




Toolless door gap adjustment

- Easy to compensate any door gaps that might occur during installation
- Adjustment button designed for smooth, hand-operated adjustment



Titus damper inside

- Push latch S2 and S3 version ensure controlled, soft and silent door opening
- Smooth user experience without door rebound
- Cushioned door landing




Reliable performance

- Reliable door opening and closing through the life-time

Push Latch S3

For all door types



Push Latch S3 with housing

Tehnickal details

Item number

Dusty white

Anthracite



Black

915.9277 →


356

383

390




Linear mounting plate




200 Sets Made of plastic

Fixing screws for mounting plates





Euro screws
821.6323.050
5000 Pcs




Chipboard screws
820.6328.050
10000 Pcs


- Soft and silent push opening
- Door gap adjustment ensures reliable closing and consistent performance
- 'Safety click' feature for easy detachment of the mechanism from its mounting plate
- Lip on the mounting plate assures accurate positioning





Drilling pattern




Mounting



Depth adjustment



Positioning




Mounting position close to the 'touch opening point' on the side opposite to hinges.

For application on cabinets with more than 2 hinges and cabinets with narrow doors we recommend a trial mounting.

Push Latch S3

For wood doors



Tehnical details

Item number

Dusty white

Anthracite

Black


Push Latch S3 drill-in

915.9276 →

356

383

390



 200 Sets Made of plastic


Drilling jig for Push Latch S3 drill-in




915.9900.072

 1 Pc


- Soft and silent push opening
- Door gap adjustment ensures reliable closing and consistent performance
- Positioning lip assures accurate position




Drilling pattern




Mounting



Depth adjustment



Positioning




Mounting position close to the 'touch opening point' on the side opposite to hinges.

For application on cabinets with more than 2 hinges and cabinets with narrow doors we recommend a trial mounting.

Push Latch S2

For wood doors



Push Latch S2



Push Latch S2



Linear mounting plate with lip

 200 Sets Made of steel and plastic

Item number

Silver grey

915.0W34 →


381

Set consists of:




 200 Sets

Fixing screws for mounting plates





Euro screws
821.6323.050
 5000 Pcs




Chipboard screws
820.6328.050
 10000 Pcs

- Soft, silent and bounce-free push opening and closing
- Safety detachment feature of the mechanism from its mounting plate
- Depth adjustment assures reliable and consistent push-to-open action
- Compatibility with damped or non-damped hinges ensures soft landing of the door


i Push latch S2 works with standard hinges with and without damping




Drilling pattern




Mounting



Depth adjustment



Positioning




Mounting position close to the 'touch opening point' on the side opposite to hinges.

For application on cabinets with more than 2 hinges and cabinets with narrow doors we recommend a trial mounting.

Push Latch

For wood doors and drawers



Push Latch



Push Latch



Cruciform mounting plate



Linear mounting plate

200 Pcs


Made of steel and plastic

- With bumper
- With bumper
- With magnet
- Linear mounting plate
- Cruciform mounting plate

Spring force [N] (released)	Spring force [N] (loaded)	Item number	Silver grey
10	20	915.0X59 →	381
13	27	915.0320 →	381
10	20	915.0D22 →	381
		915.4175 →	381
		915.4183 →	381
Sets:			
Cruciform m. plate		Linear m. plate	
915.0X59.381.K1		915.0X59.381.K2	
200 Sets		200 Sets	
915.0D22.381.K1		915.0D22.381.K2	
200 Sets		200 Sets	


Fixing screws for mounting plates

Accessories for Push latch with magnet (nickel plated steel)



Euro screws
821.6323.050


5000 Pcs



Chipboard screws
820.6328.050

10000 Pcs


Counter plate self adhesive



A = Ø15

915.7159.050 500 Pcs

Counter plate




A = Ø10 B = Ø5

915.7196.050 500 Pcs

A = Ø15 B = Ø8

915.7190.050 500 Pcs

Knock-in Counter plate





A = Ø10 B = Ø2.8

915.7199.050 500 Pcs

- Effortless opening with just a light touch
- Depth adjustment ensures reliable closing and consistent performance in case of inaccurate drilling
- 'Safety click' feature for easy detachment of the mechanism from its mounting plate




i Push latch with bumper works with standard hinge
Push latch with magnet works with reverse spring hinges or unsprung hinges




Drilling pattern

Dimensions

Depth adjustment



Positioning




Mounting position close to the 'touch opening point' on the side opposite to hinges.

For application on cabinets with more than 2 hinges and cabinets with narrow doors we recommend a trial mounting.


Tekform Slimline+ Drawer

Tekform Slimline+ Drawer




Swift assembly with enhanced front panel engagement

- Improved front panel connection ensures secure engagement and effortless disengagement



3D drawer front alignment with easy access

- Convenient front access for side, height, and tilt adjustment
- Color-coded adjustment cams for easy identification
- Ensures uniform gap layouts for evenly aligned drawer fronts




Tilt adjustment

- Accessible at the front of the drawer side
- For an intuitive drawer front positioning through the mechanical stop




Smooth and effortless performance

- Titus Damper Inside with ART function for smooth and controlled movement, regardless of the closing speed
- Low pull-out force
- Optimal closing performance and life-long consistent damping



Push-to-open compatibility for handleless cabinets

- Intuitive mounting without pre-drilling
- One-for-all: one mechanism for all Tekform Slimline+ drawers from 350mm onwards
- Easily adjustable push-to-open activation with only 1.5mm gap to operate
- Same runner for standard and push-to-open application







EasyFix front panel attachment

- Simple hand insertion
- Comfortable locking action at 90° turn of screwdriver
- Expando function for firm and reliable front attachment

Tekform Slimline+ Drawer

Product Guide

Page


Tekform Slimline+ Drawer		Side material	Drawer type	
Tekform Slimline+ drawer DW70		Metal	Soft closing Push-to-open compatible	3.13
Tekform Slimline+ drawer DW100		Metal	Soft closing Push-to-open compatible	3.15
Tekform Slimline+ drawer DW145		Metal	Soft closing Push-to-open compatible	3.17
Tekform Slimline+ drawer DW182		Metal	Soft closing Push-to-open compatible	3.19

Page

Inner Drawer Front for Tekform Slimline+ Drawer


Inner drawer front for
Tekform Slimline+ Drawer
DW70

3.21




Inner drawer front for
Tekform Slimline+ Drawer
DW145 with bar

3.23



Inner drawer front for
Tekform Slimline+ drawer
DW182 with bar

3.25




Accessories

Tacto 2.0 3.27

Marking jig 3.28

Tekform Slimline Drawer

Tekform Slimline drawer DW45



Side material	Drawer type
Metal	Soft closing Push-to-open compatible

3.29

Tekform Slimline+ Drawer

Information

Technical Guide

How to choose the appropriate drawer dimension?


Select the drawer size based on the available cabinet space. Please refer to the chart below, which indicates the

minimum space required in the cabinet to choose the appropriate drawer system.

NL = Tekform Slimline+ drawer nominal length (mm)

NL	270	300	350	400	450	500	550
----	-----	-----	-----	-----	-----	-----	-----

	Tekform Slimline+ drawer	
	Min. height H required	Cabinet depth D
Tekform Slimline+ drawer DW70	115mm	NL + min. 3mm
Tekform Slimline+ drawer DW100	147mm	NL + min. 3mm
Tekform Slimline+ drawer DW145	198mm	NL + min. 3mm
Tekform Slimline+ drawer DW182	230mm	NL + min. 3mm




How to fix drawer sides to the front panel?

The Tekform Slimline+ drawer is available with EasyFix or screw-in front connectors




Screw-in front connector

- reliable connection
- fixing with Ø3.5x15mm screws (screws are not included)



EasyFix front connector

- hand insertion
- quarter turn locking system
- expandable dowel
- easy assembly and disassembly of front panel



Planning

Bottom panel and back panel cutting dimensions

Dimensions of bottom and back panel depends on:

- cabinet width
- nominal drawer length
- drawer height

NL = Tekform Slimline+ drawer nominal length (mm)


NL	270	300	350	400	450	500	550
----	-----	-----	-----	-----	-----	-----	-----

Cabinet width

ECW: External cabinet width

ICW: Internal cabinet width


NL: Nominal length of drawer




Back panel cutting dimensions

Back panel height depends on the selected drawer height

	K
DWD70	68
DWD100	100
DWD145	151
DWD182	183



Bottom panel cutting dimensions



NL	270	300	350	400	450	500	550
L	260	290	340	390	440	490	540
L _{st}	250	280	330	380	430	480	530

NL = Slimline+ drawer nominal length (mm)

L = Length in case of wood back panel

L_{st}: Length in case of steel back panel

*For drawers with steel back panel L = NL - 20

Tekform Slimline+ Drawer

Information


Technical Guide

How to choose the appropriate drawer runner fixing positions?

The drawer's fixing position depends on its functional placement.


Tekform Slimline+ drawer front positioned outside the carcass

When the drawer front is positioned outside the carcass, use the third hole on the drawer runner for fixing.




Tekform Slimline+ drawer front positioned inside the carcass

When the drawer front is positioned inside the carcass, use the second hole on the drawer runner for fixing.



Load capacity


Drawer load capacity is 40 kg.



Expanded tolerances

Tekform Slimline+ drawer provides wider tolerances in cabinet construction and assures:

- precise drawer alignment
- smooth and silent operation
- improved drawer stability in open position
- Tekform Slimline+ drawer provides a tolerance of +/- 1mm on bottom panel width size






Adjustment needs to be done on both sides of the drawer

Adjustments



How to adjust the drawer front panel?

The Tekform Slimline+ drawer offers effortless three-dimensional front panel alignment, providing convenient access for side, height, and tilt adjustment positioned

at the front of the drawer side. Enhanced with color-coded adjustment cams, for easy identification and precise alignment, guaranteeing uniform gap layouts.





Side adjustment





Side adjustment is done by rotating the grey colored cam adjuster on the drawer side.

Height adjustment



Height adjustment is done by rotating the red colored cam adjuster on the drawer side.

Tilt adjustment




Tilt adjustment is done by rotating the yellow colored cam adjuster on the drawer side.

Tekform Slimline+ Drawer Information


Key Design Choices

ConfidentClose


Fast closing



Late start of damping



Quiet landing




CAF Consumer Assembly Friendliness

EasyFix front panel connector with expandable dowels provides:


- Quick, toolless insertion
- Quarter turn lock
- Repeatable assembly and disassembly

Front connector



Compatible with Tacto push-opening system:


- For convenient, handle-free opening
- Same runner for both, standard and Tacto push-to-open applications
- The Tacto mechanism can be simply added as a retrofit option at any time after the drawer assembly
- For all drawers from a 300mm nominal length onwards



Titus Damper inside

Designed and produced in-house


- Reliable and consistent lifelong damping
- Smooth closing
- Consistent damping performance guaranteed across high-volume production runs
- 100% automated quality check



Damping action

Even and smooth soft closing action

- Soft and reliable closing



Response to speed


Response to speed defines the increase in damping force in relation to the closing speed of the damping object.

Standard




The damping force increase is approximately linear to the increasing speed of closing.

ART - Adaptive Response Technology


Adaptive Response Technology fine-tunes the damper's performance and damping force by adjusting to the drawer's weight and speed. It provides smooth and reliable damping at any closing speed, while reducing the force needed to open the drawer.




Tekform Slimline+ Drawer DW70




Cutting dimensions details



ECW: External cabinet width
ICW: Internal cabinet width
NL: Nominal length of drawer
L_{st}: Length in case of steel back panel



4 sets

	NL	with Screw-in front connector		
	Nominal length (mm)			
			White	Anthracite
	Item number for a set			
	270	656.8352 →	150	185
	300	656.8353 →	150	185
	350	656.8354 →	150	185
	400	656.8356 →	150	185
	450	656.8357 →	150	185
	500	656.8358 →	150	185
	550	656.8359 →	150	185
One set consists of				
Drawer sides			2 pcs	
Drawer runners			2 pcs	
Front connectors			2 pcs	
Rear connectors			2 pcs	
Decorative covers			2 pcs	
Mounting instructions			1 pc/4 sets	

Push opening



Tacto Slimline Mechanism
→ see page 3.27

EasyFix front connector




656.0H66.380.00




400 Pcs

- Drawer runner type
- Load capacity
- Minimum height space required
- Drawer side thickness
- Wooden back panel thickness
- Wooden bottom panel thickness


full extension
40 kg
115mm
14mm
16mm
16mm



Side
adjustment
+1.5/-1.5 mm



Height
adjustment
+1.5/-1.5 mm



Tilt
adjustment




Works with
Tacto Push Opening Mechanism
→ see page 3.27

For further explanation → see page 3.10

Installation dimensions and drillings

Drawer runner fixing positions


Front panel




NL=270mm
NL=300mm
NL=350mm
NL=400mm
NL=450mm



Back panel





NL=500mm
NL=550mm





Assembly instructions, adjustments



Tekform Slimline+ Drawer DW100



Cutting dimensions details



4 sets

NL	with Screw-in front connector	Nominal length (mm)	Item number for a set	White	Anthracite
270	656.8360 →	150	185		
300	656.8361 →	150	185		
350	656.8362 →	150	185		
400	656.8363 →	150	185		
450	656.8364 →	150	185		
500	656.8365 →	150	185		
550	656.8366 →	150	185		
One set consists of					
Drawer sides		2 pcs			
Drawer runners		2 pcs			
Front connectors		2 pcs			
Rear connectors		2 pcs			
Decorative covers		2 pcs			
Mounting instructions		1 pc/4 sets			

Push opening



Tacto Slimline Mechanism
→ see page 3.27

EasyFix front connector




656.0H66.380.00


400 Pcs

- Drawer runner type
- Load capacity
- Minimum height per drawer required
- Drawer side thickness
- Wooden back panel thickness
- Wooden bottom panel thickness


full extension
40 kg
147mm
14mm
16mm
16mm



Side
adjustment
+1.5/-1.5 mm



Height
adjustment
+1.5/-1.5 mm



Tilt
adjustment




Works with
Tacto Push Opening Mechanism
→ see page 3.27

For further explanation → see page 3.10

Installation dimensions and drillings

Drawer runner fixing positions


Front panel




NL=270mm
NL=300mm
NL=350mm
NL=400mm
NL=450mm



Back panel





NL=500mm
NL=550mm





Assembly instructions, adjustments






Tekform Slimline+ Drawer DW145



Cutting dimensions details




	NL	with Screw-in front connector		
	Nominal length (mm)			
				
		Item number for a set	White	Anthracite
	270	656.8367 →	150	185
	300	656.8368 →	150	185
	350	656.8369 →	150	185
	400	656.8370 →	150	185
	450	656.8371 →	150	185
	500	656.8372 →	150	185
	550	656.8373 →	150	185
One set consists of				
Drawer sides				2 pcs
Drawer runners				2 pcs
Front connectors				2 pcs
Rear connectors				2 pcs
Decorative covers				2 pcs
Mounting instructions				1 pc/4 sets




- Drawer runner type
- Load capacity
- Minimum height per drawer required
- Drawer side thickness
- Wooden back panel thickness
- Wooden bottom panel thickness


full extension
40 kg
198mm
14mm
16mm
16mm



Side
adjustment
+1.5/-1.5 mm



Height
adjustment
+1.5/-1.5 mm



Tilt
adjustment




Works with
Tacto Push Opening Mechanism
.....> see page 3.27

For further explanation → see page 3.10


Installation dimensions and drillings

Drawer runner fixing positions


Front panel




NL=270mm
NL=300mm
NL=350mm
NL=400mm
NL=450mm



NL=500mm
NL=550mm



Back panel





Assembly instructions, adjustments







*A trial mounting is always recommended.
For further information please contact your
Titus Group representative.*

Tekform Slimline+ Drawer DW182



Cutting dimensions details



NL	with Screw-in front connector	Nominal length (mm)	Item number for a set	White	Anthracite
270	656.8374 →	150	185		
300	656.8375 →	150	185		
350	656.8376 →	150	185		
400	656.8377 →	150	185		
450	656.8378 →	150	185		
500	656.8379 →	150	185		
550	656.8380 →	150	185		
One set consists of					
Drawer sides				2 pcs	
Drawer runners				2 pcs	
Front connectors				2 pcs	
Rear connectors				2 pcs	
Decorative covers				2 pcs	
Mounting instructions				1 pc/4 sets	



Push opening

Tacto Slimline Mechanism

→ see page 3.27



EasyFix front connector

656.0H67.380.00


 400 Pcs

3.19


Titus

- Drawer runner type
- Load capacity
- Minimum height per drawer required
- Drawer side thickness
- Wooden back panel thickness
- Wooden bottom panel thickness


full extension
40kg
230mm
14mm
16mm
16mm



Side
adjustment
+1.5/-1.5 mm



Height
adjustment
+1.5/-1.5 mm



Tilt
adjustment




Works with
Tacto Push Opening Mechanism
.....> see page 3.27

For further explanation → see page 3.10


Installation dimensions and drillings

Drawer runner fixing positions

Front panel





NL=270mm
NL=300mm
NL=350mm
NL=400mm
NL=450mm



NL=500mm
NL=550mm



Back panel




Assembly instructions, adjustments




*A trial mounting is always recommended.
For further information please contact your
Titus Group representative.*

Inner Drawer Front for Tekform Slimline+ Drawer DW70



Front panel



Cutting dimension L = ICW-105
ICW → see page 3.22



20 pcs

Made of aluminium



Front bracket




50 sets

Made of aluminium and plastic


External cabinet width	Item number		
		White	Antracite grey
600	656.8048 →	511	515
1200	656.8053 →	511	515
	656.8334 →	350	385



Side
adjustment
+1.5/-1.5 mm



Height
adjustment
+1.5/-1.5 mm




Tilt
adjustment

For further explanation → see page 3.10

Installation dimensions

Drawer runner fixing positions


Cutting dimensions details




ECW: External cabinet width
ICW: Internal cabinet width
NL: Nominal length of drawer



NL=270mm
NL=300mm
NL=350mm
NL=400mm
NL=450mm




NL=500mm
NL=550mm




Assembly instructions, adjustments



Inner Drawer Front for Tekform Slimline+ Drawer DW145 with Bar



Front bar




Cutting dimension L = ICW-94
ICW → see page 3.24



50 pcs

Made of aluminium

Front panel



Cutting dimension L = ICW-105
ICW → see page 3.24



20 pcs

Made of aluminium



Front bracket



20 pcs

Made of aluminium and plastic

ECW	External cabinet width	Item number		
			White	Antracite grey
600	656.8126 →	511	515	
1200	656.8132 →	511	515	
600	656.8048 →	511	515	
1200	656.8053 →	511	515	
	656.8337 →	350	385	




For further explanation → see page 3.10


Installation dimensions

Drawer runner fixing positions


Cutting dimensions details




ECW: External cabinet width
ICW: Internal cabinet width
NL: Nominal length of drawer



NL=270mm
NL=300mm
NL=350mm
NL=400mm
NL=450mm




NL=500mm
NL=550mm



Assembly instructions, adjustments



Inner Drawer Front for Tekform Slimline+ Drawer DW182 with Bar



Front bar




Cutting dimension L = ICW-94
ICW → see page 3.26



50 pcs

Made of aluminium and plastic

Front panel



Cutting dimension L = ICW-105
ICW → see page 3.26



20 pcs

Made of aluminium



Front bracket



20 sets

Made of aluminium and plastic

ECW	External cabinet width	Item number		
			White	Antracite grey
600	656.8126 →	511	515	
1200	656.8132 →	511	515	
600	656.8048 →	511	515	
1200	656.8053 →	511	515	
	656.8341 →	350	385	




For further explanation → see page 3.10


Installation dimensions

Drawer runner fixing positions


Cutting dimensions details




ECW: External cabinet width
ICW: Internal cabinet width
NL: Nominal length of drawer



NL=270mm
NL=300mm
NL=350mm
NL=400mm
NL=450mm



NL=500mm
NL=550mm




Assembly instructions, adjustments




TouchControl Solutions

Tacto 2.0



- Intuitive mounting
- One-for-all – One item fits all Slimline+ drawers from NL=300mm
- Easily adjustable push-to-open activation with only 1.5mm gap to operate
- Easy opening, reliable closing




Tacto 2.0

Technical details

Item number for set

656.9220.383.K1



One set consists of

PushOpen Mechanism



2 pcs

Tacto Activator



2 pcs

Chipboard screws



4 pcs/set

Mounting instructions



1 pc/set

Assembly instructions, adjustments




30 sets





Made of plastic

Accessories

Marking Jig





Tekform Slimline+ Drawer


		Item number	Black
Marking jig for Tekform Slimline+ drawer DW70 and DW100  1  2   1 set Made of plastic and steel		656.9339	390
Marking jig for Tekform Slimline+ drawer DW145 and DW182  1  2   1 set Made of plastic and steel		656.9340	390

Tekform Slimline DW45


Shallow Drawer



Cutting dimensions details



ECW: External cabinet width
 ICW: Internal cabinet width
 NL: Nominal length of drawer
 L_{st}: Length in case of steel back panel



L_{st}: NL - 20
 For further explanation
 → see page 3.8

NL	with Screw-in front connector		
Nominal length (mm)		White	Anthracite
	Item number for a set		
450	655.8046	150	185
500	655.8047	150	185
To be ordered separately Steel back panel			
600*	655.7273	150	185
* cabinet side thickness 18mm			
One set consists of			
Drawer sides		2 pcs	
Drawer runners		2 pcs	
*Front connectors		2 pcs	
Covers		2 pcs	
Mounting instructions		1 pc/4 sets	

Screws are not included

- Drawer runner type
- Load capacity
- Minimum height space required
- Back panel
- Wooden bottom panel thickness

full extension
40 kg
76mm
steel
16mm




Side
adjustment
+1/-1mm


i Works with or without
Tacto Mechanism

Installation dimensions

Minimum space required for the
cabinet





Drawer runner fixing positions



Drilling dimensions for the front panel

Screw-in attachment



Titus Group

Products. People. Relationships.

We are proud to support furniture manufacturers, designers, distributors and OEM partners worldwide with solutions that are precise, reliable and simple to work with.

From our engineering centres to your production line, and from first contact to long-term support, we're here to help you build better – with less complexity, more clarity, and total confidence.

Titus Group designs and manufactures precision-engineered components that simplify furniture assembly, improve functionality, and ensure long-term reliability. Our core solutions – including connectors, hinges, dampers, soft-close systems, and drawer technologies – are trusted by manufacturers across a wide range of industries, from furniture and kitchens to home appliances and beyond.

With engineering, manufacturing, and customer support facilities across **Europe, Asia, North America, and Australasia**, we combine global consistency with local responsiveness.

Our vertically integrated operations support fast development, reliable delivery, and consistently high quality across markets.

For decades, we have been driven by a clear principle: **Engineered for Purpose**. This defines how we design, how we manufacture, and how we collaborate with our partners. Through **engineering simplicity**, we help our customers work more efficiently, reduce complexity, and bring better products to market – with confidence and consistency.

1973

Titus established

1975

Revolution in particleboard panel processing productivity

1977

Titus launches concealed cabinet connector

1980

Titus USA office and manufacturing established

1990

Launch of innovative Quickfit technology

2005

Titusonic ultrasound fastening technology introduced

2006

Merger with Lama d.d.
Launch of Glissando

2007

Titus becomes Titus+
Specialist in precision components engineering

2009

Damper development and engineering

2014

Acquisition of Tekform, Australia

2017

Launch of T-type full hinge programme

2019

Launch of TeraBlack product range

2020

Acquisition of Simon Kinetics, Germany

2022

Acquisition of Titus Precision, USA

2023

Launch of T-type PressTo toolless mounting

Our Vision



To be the world's best in engineering for precision components.

Our Mission

To provide manufacturers with component solutions that improve their competitiveness.

Our Principles

- Gain total knowledge of our customers and their markets.
- Focus on identifying and creating high-volume component niches.
- Meet our customers' expectations with global consistency.
- Build long-term associations with customers, suppliers, colleagues and shareholders.
- Invest in the abilities of individuals at every level.
- Continuously enhance input efficiency and sustainability.
- Provide equal opportunities to all.



Product Groups

Cabinet Hardware

Cabinet connectors, concealed hinges, soft-close systems, kitchen drawers and accessories, RV hardware



Damping and Kinetics

Hydraulic dampers and Slidix soft-close systems for custom applications in home equipment



Titus Technologies

Automated assembly systems
Die casting technologies
Titusonic – Ultrasound fastening
FastFit insertion technology



Totally Integrated Engineering


At Titus, **Totally Integrated Engineering** means bringing together product design, proprietary manufacturing technologies, and fully controlled in-house operations into a single, seamless process. This integrated approach allows us to develop, produce, and deliver precision-engineered components that are consistent, reliable, and tailored to purpose.

It's not just about what we do – it's how we do it. By maintaining control across the entire development and production chain, we deliver measurable advantages to our customers: consistent product quality, faster time to market, and meaningful product benefits that lower total installed cost.

Our approach is guided by a set of core principles that define who we are and how we operate:


Manufacturing Operations

Fully controlled in-house operations
A wide range of proprietary technologies and services enabling high-volume production of precision components with consistency and speed.




Manufacturing Technologies

Process optimisation through proprietary innovation
Advanced manufacturing technologies that increase productivity, ensure repeatable quality, and support scalable growth.




Precision Components

Engineered for consistency, reliability, and purpose
Precision components designed to meet exacting performance standards – delivering built-in value from concept to final assembly.



Product Design

Component design for repeatable excellence
Unique components engineered for consistent quality, functional simplicity, and efficient integration into high-volume systems.



Engineered for Purpose

At **Titus Group**, engineering is never about excess. It's about intention. Every product, every feature, every process is developed with a clear purpose: to solve a real problem and deliver lasting value.

Engineered for Purpose is more than a slogan – it's our mindset.

It defines how we innovate, how we manufacture, and how we collaborate.

Focused on what matters

We don't follow trends for the sake of it. We listen to our customers, understand their needs, and deliver what works. Our solutions are built to perform in the real world – in real kitchens, real bedrooms, real production lines.

This focus allows us to eliminate unnecessary complexity and design components that are not only technically advanced, but also intuitive and dependable.

A solution provider, not just a manufacturer

We go beyond hardware. We work alongside our customers to co-create solutions that integrate seamlessly into their production processes and business models. From idea to implementation, we ensure speed, precision, and consistency — globally.

Whether it's:

- Developing smart connectors that tolerate drilling inaccuracies,
- Designing hinges that make tall doors align effortlessly, or
- Engineering soft-close systems that deliver just the right resistance,


... we always have a purpose in mind: to make furniture manufacturing easier, faster, and more competitive.

Built on experience. Proven by performance.

We apply decades of engineering knowledge across industries and markets, ensuring that our solutions are both reliable and scalable. Every new product is tested, refined, and validated to ensure that it performs consistently – across regions, materials, and applications.

Because to us, engineered for purpose means engineered for you.

Titus Group Companies Worldwide



This map shows Titus Group companies only. For distribution partners, visit titusplus.com.

 Made in USA - product manufactured in the USA.

Engineered for Purpose

Titus is committed to providing its customers with products and services that improve their competitiveness, while reducing manufacturing and assembly costs.

Index

Item number	Page
00022	1.17
00062	1.11
00068	1.11
00071	1.11
00077	1.11
00172	1.11
00180	1.10
006661	1.46
006663	1.46
006665	1.46
006667	1.46
01020	1.11
01026	1.36
01029	1.36
01042	1.11
01056	1.11
01825	1.53
01838	1.53
01843	1.53
01912	1.53
01924	1.54
01927	1.54
02077	1.12
02120	1.18
02190	1.17
02254	1.55
02523	1.51
02558	1.52
02559	1.52
02560	1.52
02570	1.51
02571	1.51
02653	1.51
02666	1.51
03090	1.14
03118	1.14
03165	1.14
03181	1.14
0435	1.45
0436	1.45
05025	1.30
05026	1.30
05050	1.30
05052	1.30
05147	1.30
05388	1.29
05414	1.31
05441	1.29
05474	1.29
05753	1.33
05757	1.33
05778	1.33
05917	1.47

Item number	Page
05929	1.33
05960	1.47
05971	1.47
06074	1.11
06077	1.11
06080	1.11
06309	1.53
06343	1.45
06348	1.45
06381	1.42
06383	1.42
06385	1.42
06387	1.42
06389	1.41
06395	1.43
06397	1.43
06401	1.40
06402	1.40
06406	1.40
06408	1.39
06414	1.41
06416	1.41
06439	1.43
06447	1.42
06449	1.42
06455	1.43
06457	1.43
06465	1.44
06471	1.44
06472	1.44
06473	1.44
06479	1.39
06802	1.16
06803	1.16
09423	1.32
09424	1.32
09456	1.32
09495	1.35
09533	1.35
09536	1.35
09537	1.35
09592	1.32
09594	1.32
09651	1.28
09652	1.28
09690	1.34
09692	1.34
09695	1.34
09699	1.34
242.0970.054	2.67
242.0976.054	2.67
242.0997.054	2.67
242.0A00.054	2.67

Item number	Page
242.0G76.650	2.71
242.0P81.650	2.69
242.0Y45.650	2.73
244.0266.050	2.90
244.0085.650	2.92
244.0095.650	2.92
244.0118.050	2.92
244.0119.050	2.92
244.0134.050	2.92
244.0135.050	2.92
244.0136.050	2.92
244.0137.050	2.92
244.0166.050	2.92
244.0167.050	2.92
244.0258.050	2.90
244.0260.050	2.90
244.0261.050	2.90
244.0263.050	2.90
244.0264.050	2.90
244.0270.050	2.90
244.0272.050	2.90
244.0342.050	2.90
244.0344.050	2.90
244.0M33.650	2.92
244.0P26.050	2.92
244.0P27.050	2.92
244.0P29.650	2.92
244.0Z26.050	2.92
244.1136.050	2.92
244.1139.050	2.92
244.1233.050	2.92
244.1234.050	2.92
244.3016.650	2.92
244.3651.650	2.92
244.3653.650	2.94
244.3654.650	2.94
244.3655.650	2.94
248.0162.050	2.85
248.0171.050	2.75
248.0279.050	2.75
248.0280.050	2.75
248.0285.050	2.79
248.0433.050	2.77
248.0535.050	2.75
248.0536.050	2.75
248.0537.050	2.75
248.0745.050	2.81
248.0M73.050	2.83
248.0N16.050	2.77
248.0N20.050	2.79
248.0N24.050	2.81
248.0R14.050	2.83
248.0U21.050	2.87

Item number	Page
248.0U22.050	2.87
248.1646	2.97
248.1712	2.97
248.4668	2.95
248.4672	2.95
338.9721	1.53
655.7273	3.29
655.8046	3.29
655.8047	3.29
656.0H66.380.00	3.13, 3.15
656.0H67.380.00	3.17, 3.19
656.8048	3.21, 3.23, 3.25
656.8053	3.21, 3.23, 3.25
656.8126	3.23, 3.25
656.8132	3.23, 3.25
656.8334	3.21
656.8337	3.23
656.8341	3.25
656.8352	3.13
656.8353	3.13
656.8354	3.13
656.8356	3.13
656.8357	3.13
656.8358	3.13
656.8359	3.13
656.8360	3.15
656.8361	3.15
656.8362	3.15
656.8363	3.15
656.8364	3.15
656.8365	3.15
656.8366	3.15
656.8367	3.17
656.8368	3.17
656.8369	3.17
656.8370	3.17
656.8371	3.17
656.8372	3.17
656.8373	3.17
656.8374	3.19
656.8375	3.19
656.8376	3.19
656.8377	3.19
656.8378	3.19
656.8379	3.19
656.8380	3.19
656.9220.383.K1	3.27
656.9339	3.28
656.9340	3.28
700.0KA0.054	2.60
700.0KA3.054	2.60

Index

Item number	Page
700.0KB0.054	2.60
700.0KB3.054	2.60
700.0KC0.054	2.60
700.0KC3.054	2.60
700.0KF0.054	2.60
700.0KF3.054	2.60
700.0KW0.650	2.64
700.0KW3.650	2.64
700.0KW6.650	2.64
700.0KWN.054	2.64
700.0LB0.650	2.60
700.0LB3.650	2.60
700.0LC0.650	2.60
700.0LC3.650	2.60
700.0LF0.650	2.60
700.0LF3.650	2.60
700.0NA0.054	2.62
700.0NA3.054	2.62
700.0NB0.054	2.62
700.0NB3.054	2.62
700.0NC0.054	2.62
700.0NC3.054	2.62
700.0NE0.054	2.62
700.0NE3.054	2.62
700.0NF0.054	2.62
700.0NF3.054	2.62
701.0895.650	2.33
701.0899.650	2.31
701.0A96.650	2.33
701.0AT0.054	2.25
701.0AT1.054	2.25
701.0AT5.054	2.25
701.0AT6.054	2.25
701.0B08.650	2.31
701.0BT0.054	2.25
701.0BT1.054	2.25
701.0BT5.054	2.25
701.0BT6.054	2.25
701.0BY9.650	2.29
701.0C78.650	2.31
701.0CT0.054	2.27
701.0CT1.054	2.27
701.0CT5.054	2.27
701.0CT6.054	2.27
701.0D36.650	2.33
701.0D82.650	2.29
701.0D88.650	2.29
701.0DT0.054	2.27
701.0DT1.054	2.27
701.0DT5.054	2.27
701.0DT6.054	2.27
701.0ET0.054	2.37
701.0ET1.054	2.37

Item number	Page
701.0ET5.054	2.37
701.0ET6.054	2.37
701.0FT0.054	2.39
701.0FT1.054	2.39
701.0FT5.054	2.39
701.0FT6.054	2.39
701.0GT0.054	2.39
701.0GT1.054	2.39
701.0GT5.054	2.39
701.0GT6.054	2.39
701.0UT0.054	2.35
701.0UT1.054	2.35
701.0UT5.054	2.35
702.0689.650	2.49
702.0797.650	2.45
702.0879.650	2.47
702.0A95.650	2.49
702.0AK0.054	2.41
702.0AK1.054	2.41
702.0AK5.054	2.41
702.0B07.650	2.47
702.0BK0.054	2.41
702.0BK1.054	2.41
702.0BK5.054	2.41
702.0C77.650	2.47
702.0CK0.054	2.43
702.0CK1.054	2.43
702.0CK5.054	2.43
702.0D35.650	2.49
702.0D81.650	2.45
702.0D87.650	2.45
702.0DK0.054	2.43
702.0DK1.054	2.43
702.0DK5.054	2.43
702.0EK0.054	2.53
702.0EK1.054	2.53
702.0EK5.054	2.53
702.0FK0.054	2.55
702.0FK1.054	2.55
702.0FK5.054	2.55
702.0GK0.054	2.55
702.0GK1.054	2.55
702.0GK5.054	2.55
702.0UK0.054	2.51
702.0UK1.054	2.51
702.0UK5.054	2.51
721.0PK0.650	2.57
721.0PK5.650	2.57
728.1283	2.97
728.1284	2.97
728.1286	2.97
728.1287	2.97
728.4669	2.95

Item number	Page
729.0K71.054	2.107
820.6308.050	2.67, 2.69, 2.71, 2.73, 2.75, 2.77, 2.79, 2.81, 2.83, 2.85, 2.87
820.6328.050	2.25, 2.27, 2.29, 2.31, 2.33, 2.35, 2.37, 2.39, 2.41, 2.43, 2.45, 2.47, 2.49, 2.51, 2.53, 2.55, 2.57, 2.61, 2.63, 2.91, 2.93, 2.119, 2.123, 2.125
821.6304.050	2.91
821.6323.050	2.91, 2.119, 2.123, 2.125
821.6332.050	2.91
915.0320	2.125
915.0D22	2.125
915.0D22.381.K1	2.125
915.0D22.381.K2	2.125
915.0W34	2.123
915.0X59	2.125
915.0X59.381.K1	2.125
915.0X59.381.K2	2.125
915.4175	2.125
915.4183	2.125
915.7159.050	2.125
915.7190.050	2.125
915.7196.050	2.125
915.7199.050	2.125
915.9276	2.121
915.9277	2.119
915.9900.072	2.121
951.0D45.054	2.107
951.0F15.650	2.109
972.0F09	2.113
972.0X19	2.111
972.0X21	2.113
972.0X34	2.111
973.0M99	2.115
973.0M99.380.K1	2.115
973.4451	2.115

Titus Group
Titus Precision
900 W Connexion Way, Columbia City, IN 46725
United States
+1 260 244 6114

Cabinet and Furniture Hardware Systems 01.1 En Jun26

Your authorized dealer

